

Interpretability in the Era of Large Language Models: Mechanistic Methodology, Empirical Practices, and Applications



Zhengfu He

Fudan University



Jieping Ye

Alibaba Group



Xu Shen


Alibaba Group

Capabilities Surge, Transparency Stalls

The capability frontier is advancing far faster than our ability to explain it — underscoring the critical need for interpretability.

CAPABILITIES

OpenAI's five levels toward AGI



- L1 Chatbots: AI with conversational language
- L2 Reasoners: AI that solves human-level problems
- L3 Agents: AI that can take actions in the world
- L4 Innovators: AI that can aid in scientific discovery
- L5 Organizations: AI that can organize into teams

Interpretability Becomes One of AI's Defining Frontiers

Dario Amodei

The Urgency of Interpretability

April 2025

In the decade that I have been working on AI, I've watched it grow from a tiny academic field to arguably the most important economic and geopolitical issue in the world. In all that time, perhaps the most important lesson I've learned is this: the progress of the underlying technology is inexorable, driven by forces too powerful to stop, but the *way* in which it happens—the order in which things are built, the applications we choose, and the details of how it is rolled out to society—are eminently possible to change, and it's possible to have great positive impact by doing so. We can't *stop* the bus, but we can *steer* it.

In the past I've written about the importance of deploying AI in a way that is positive for the world, and of ensuring that democracies build and wield the technology before autocracies do. **Over the last few months, I have become increasingly focused on an additional opportunity for steering the bus: the tantalizing possibility, opened up by some recent advances, that we could succeed at interpretability—that is, in understanding the inner workings of AI systems—*before* models reach an overwhelming level of power.**

Anthropic's Dario Amodei: we must understand AI's inner workings before models grow too powerful to steer.

Demis Hassabis Embraces the Future of Work in the Age of AI

The CEO of Google's DeepMind says systems as smart as humans are almost here—and that the job market will undergo "scary" changes.



We don't have much time. We're increasingly putting resources into security and things like cyber and also research into, you know, controllability and understanding these systems, sometimes called mechanistic interpretability.

And then at the same time, we need to also have societal debates about institutional building. How do we want governance to work? How are we going to get international agreement, at least on some basic principles around how these systems are used and deployed and also built?

DeepMind's Demis Hassabis warns time is short — controllability and interpretability are vital to deploy AI safely.



Can LLMs Explain Their Internal Mechanisms?

“Everything should be made as simple as possible, but no simpler.”

-- Albert Einstein

*“Interpretability is like an **MRI for AI**...
I am optimistic that interpretability can **reliably detect most model problems** by **2027**.”*

Dario Amodei · CEO, Anthropic ·

The Urgency of Interpretability · Apr 2025



MIT
Technology
Review

10 Breakthrough Technologies



Hyperscale AI data centers

Hyperscale
AI data centers



Sodium-ion
batteries




Sodium-ion
batteries

Base-
edited
babies




Mechanistic
interpretability




Next-gen
nuclear



AI
companions




Embryo
scoring



Gene
resurrection


Next-gen nuclear




Generative
coding




Commercial
space stations



Human Brain vs. LLM



Neural Circuit in **Human Brains**




Network Circuit in **Large Language Models**

Current estimates suggest that our comprehensive understanding of the human brain's inner workings may still be under **10%**.

The brain is incredibly complex, containing approximately **86 billion neurons** with millions of billions of connections (synapses).


Evolution of LLM Interpretability



Trend 1: The Field Is in Hypergrowth

Interpretability research is compounding — 2,678 works catalogued, and flagship-venue output has **nearly tripled** since 2021 (322 → 957 papers/yr). — and its focus has shifted to LLMs, where **mechanistic methods now grow the fastest** ($\approx 11\% \rightarrow 26\%$ of papers in two years).


Top-venue interpretability papers / year



Adopted across every top venue



Its center of gravity has moved to LLM Mechanism



Source: (1) 2021–2026 flagship venues = ACL / EMNLP / ICLR / ICML / NeurIPS; (2) selected research blogs released from frontier AI laboratories (OpenAI, DeepMind, Anthropic). Theme trends are title-keyword matches (mechanistic = SAE / circuit / superposition; CoT / reasoning; feature attribution / saliency) — a title-based lower bound.

Trend 2: A Global Push Across Industry and Academia

Driven by frontier labs, interpretability is now a global, industry-and-academia endeavor spanning many countries.

2,484
Unique institutions


6,969
Institution mentions

52
Countries / regions


Institution word cloud · size = participation frequency



Country / region distribution




Top 10 institutions



Frequency = number of times an institution appears across all listed papers & blogs (multi-affiliation papers counted per institution). Country coverage ≈75% of mentions; unmapped generic entries excluded.

Trend 3: Interpretability Scales to Frontier Models

Mechanistic evidence scaled from **toy models** to **production LLMs** (from anthropic).



Interpretable units recovered per model: **4,096** features on a 1-layer toy model (Oct 2023) → **34,000,000** on Claude 3 Sonnet (May 2024) — a **~8,000x** jump in 7 months.

Trend 4: The Expanding Applications of Interpretability

Interpretability is expanding outward — from safeguarding to shaping training, curating data, and agentic systems.



Safety

2021 →

Audit and monitor deployed models for deception, bias and misalignment.

- ▶ A Mathematical Framework for Transformer Circuits — Elhage et al., 2021
- ▶ Safety-relevant features at scale — Templeton et al., 2024
- ▶ Persona features predict emergent misalignment — OpenAI, 2025 (arXiv:2506.19823)
- ▶ Evaluation-awareness in alignment audits — Anthropic, 2025

Training

2024 →

Feed internals back into the training loop itself.

- ▶ Sparse Crosscoders: diffing checkpoints across training — Lindsey et al., 2024
- ▶ Steering during fine-tuning to prevent misalignment — OpenAI, 2025
- ▶ Model Spec midtraining for alignment generalization — Anthropic, 2026
- ▶ Gemma Scope: open SAEs enabling training analyses — DeepMind, 2024

Data

2025 →

Trace behaviors back to the corpora that produced them.

- ▶ Influence functions for LLM generalization — Grosse et al., 2023 (precursor)
- ▶ Feature-level attribution to training data — 2025
- ▶ Detecting poisoned / low-quality data slices — 2025
- ▶ Implicit curriculum: what LMs learn and when — 2026

Agentic

2026 →

Explain systems that plan, call tools and act over long horizons.


- ▶ We Can and Should Pursue Agentic Interpretability — Google, 2025
- ▶ Interpreting Agentic Systems: System-Level Accountability — 2026
- ▶ Transparency in Agentic AI: A Survey of Interpretability — 2026
- ▶ Accountable Deployment Demands Layered Interpretability — 2026

Trend 5: Understand → Monitor → Intervene on LLM Internals

The field evolved from **understanding** internal structures and **monitoring** them at scale, to ultimately **intervening** on them.

TARGET 1 · Understand

Elhage et al. 2021 · Olsson et al. 2022 · Bricken et al. 2023




dictionary learning assigns each feature a label

"What does this neuron mean?" — circuits mathematics, superposition theory and SAE dictionary learning made features human-readable.

TARGET 2 · Monitor

Templeton et al. 2024 · Lindsey et al. 2024 · OpenAI 2025




34M features under continuous monitoring

"What is it computing right now?" — 34M-feature monitoring on Claude 3 Sonnet, crosscoder checkpoint diffing, persona-feature misalignment flags.

TARGET 3 · Intervene

Anthropic Circuit Tracing 2025 · OpenAI 2025 · Anthropic 2026




feature steering · circuit editing · behavior correction

"Can we change the computation?" — persona suppression, attribution-guided circuit edits, weight-sparse interpretable-by-design training.


Trend 6: Open Interpretability Toolbox

40+ open interpretability tools, grouped into 5 paradigms — and where they cluster.



Takeaway: tooling piles up on **reading internals & sparse features**; behavior control & applied layers remain underdeveloped.

Five Levels of LLM Interpretability



Identify Primitives → Map Causal Circuits → Explain Agency → Automate Discovery → Govern Evolution

Recommended Reading List

2020 – 2023 Foundations → Features & Superposition

2020

COMMUNITY

Logit Lens

Reading hidden states through the unembedding (nostalgebraist)

2021

ANTHROPIC

A Mathematical Framework for Transformer Circuits ★

The founding framework of circuit-level analysis

2022

ANTHROPIC

In-Context Learning & Induction Heads

Circuits that explain how in-context learning emerges

2023

ANTHROPIC

Towards Monosemanticity (SAE) ★

Sparse dictionary learning extracts interpretable features

2023 – 2025 Explanation, Steering & Causal Circuits

2023

OPENAI

Language Models Can Explain Neurons

Automated, scalable neuron explanation with GPT-4

COMMUNITY

Activation Addition · ActAdd

Steering model behavior via activation vectors (Turner et al.)

COMMUNITY

Attribution Patching

Activation patching at industrial scale (Neel Nanda)

COMMUNITY

Path Patching ★

Causal path-level localization for circuit discovery (Goldowsky-Dill et al.)

2025

ANTHROPIC

Circuit Tracing · Attribution Graphs ★

Tracing computation paths through the model end-to-end

● Anthropic

● OpenAI

● Community / blog

★ must-read foundational

02 | Interpretability Basics


Overview

- Revisiting core components in a Transformer
 - Residual connections
 - MLP neurons (reading and writing from the residual stream; logit lens)
 - Attention heads (QK / OV circuit, independence & additivity)
- How we interpret each individual component
 - Top activation and LLM based automation
- How we identify important components for a given model behavior (The top down approach)
 - Activation Patching & Path patching
- The bottom-up approach of Mechanistic Interpretability
 - Sparse Autoencoders

Revisiting the Residual Streams


The residual stream perspective of a Transformer

2015 · residual block




The residual branch is visually central; the identity path looks like a bypass.

$$\mathbf{x}_{l+1} = \mathbf{x}_l + \mathbf{F}_l(\mathbf{x}_l)$$




circuit view · residual stream



The persistent state is visually central; blocks become readers and writers.


Takeaway: “what information does each component read from—and write into—the shared state?”

The residual stream perspective of a Transformer




Takeaway: Later layers can reinforce or cancel write-ins from early layers.

Aside: The exponential growth of Residual Stream norms




A mental model for language model computation

Three token positions own their independent residual-stream computation; self-attention exchanges context across the sequence.




Interpreting a single MLP neuron

MLP neurons: feature detectors that write to the stream



Logit lens: read the stream in vocabulary space

The logit lens: pause the model at an intermediate layer, take the current residual state, and ask “what next-token logits would the unembedding already give us?”



	'Other'	'(+)' times'	'(+)' ;'	'when'	'(+)' people'	'(+)' say'	'(+)' plasma'
h_out	'Plasma'	'times'	'.'	'they'	'people'	'say'	'plasma'
h46_out	'But'	'times'	'.'	'they'	'people'	'say'	'..'
h44_out	'Plasma'	'times'	'.'	'they'	'people'	'say'	'plasma'
h42_out	'Plasma'	'times'	'.'	'they'	'people'	'say'	'plasma'
h40_out	'Plasma'	'times'	'.'	'they'	'people'	'say'	'plasma'
h38_out	'Plasma'	'times'	'they'	'they'	'people'	'say'	'plasma'
h36_out	'But'	'times'	'they'	'they'	'people'	'say'	'plasma'
h34_out	'But'	'times'	'they'	'they'	'people'	'say'	'electron'
h32_out	'But'	'times'	'they'	'they'	'people'	'say'	'..'
h30_out	'But'	'times'	'they'	'they'	'people'	'say'	'..'
h28_out	'But'	'worldly'	'they'	'referring'	'people'	'say'	'..'
h26_out	'But'	'worldly'	'they'	'they'	'people'	'say'	'..'
h24_out	'But'	'worldly'	'vague'	'however'	'pressed'	'talk'	'..'
h22_out	'But'	'worldly'	'confused'	'however'	'pressed'	'want'	'..'
h20_out	'But'	'worldly'	'confused'	'perhaps'	'they'	'revol'	'..'
h18_out	'But'	'worldly'	'confused'	'perhaps'	'struck'	'thought'	'..'
h16_out	'It'	'worldly'	'confused'	'perhaps'	'struck'	'thought'	'..'
h14_out	'It'	'worldly'	'confused'	'however'	'struck'	'criticized'	'..'
h12_out	'I'	'worldly'	'warp'	'however'	'she'	'thought'	'..'
h10_out	'I'	'worldly'	'warp'	'however'	'struck'	'jammed'	'they'
h8_out	'I'	'worldly'	'cale'	'however'	'faced'	'jammed'	'certain'
h6_out	'I'	'worldly'	'cale'	'chim'	'faced'	'took'	'Duc'
h4_out	'I'	'worldly'	'cale'	'Garland'	'she'	'are'	'arte'
h2_out	'I'	'worldly'	'cale'	'I'	'traveling'	'would'	'grilled'
h0_out	'I'	'worldly'	'times'	'but'	'traveling'	'oner'	'goodbye'

Logit Lens: $\text{logits}_l = \text{Unembed}(\text{LN}(x_l))$ Stop at layer l and decode the current state.

From logit lens to interpreting an MLP neuron

Natural question: if one MLP neuron fires, what did it detect, and what does its write push the model toward saying?

neuron 1: say capital cities

output perspective: vocabulary push

Project the neuron's write through the unembedding.
Which token directions receive positive logit pressure?



- Paris +
- Tokyo +
- capital +

output label is not enough; it is one side of the explanation

neuron 2: Thank you


TOP ACTIVATIONS	
you 290.98	Or , are these too far from Zheng zhou ? Dear Guest , Thank you for your question . And sorry f works
thank 289.73	bed area . Overall we were happy with our stay . Hi Ladd - thank you for your kind review ! We are gla
Thank 269.04	. Apartments are comfortable . Continue with the good Dear Carlos , Thank you for taking the time to write i
you 263.26	The unit was clean and well maintained . Owner ' s reply : Thank you for the nice review . It wa
thank 259.14	The renders above are looking amazing . The skin mate Hi Tyler , thank you ! Actually I ´ m living in Teruel
thank	2.6 years of experience in custom - clothing .

Takeaway: a neuron interpretation should connect **when it activates** to **what residual-stream direction it writes**; logit lens gives the vocabulary-facing readout.

Sources: nostalgebraist (2020), "interpreting GPT: the logit lens"; Elhage et al. (2021), A Mathematical Framework for Transformer Circuits.

AutoInterp: scaling MLP-neuron interpretation

Manual reading works for one neuron: top activations show when it fires; logit lens shows what its write pushes. AutoInterp turns that loop into a scalable hypothesis-and-test workflow.




Bridge: residual-stream additivity lets us inspect an MLP neuron as one write; **top activations** provide input evidence, while **logit lens** provides output-side evidence.

Interpreting a single Attention head

Attention heads: independence and additivity


Key reframing: the standard implementation fuses heads for a faster matrix multiply; mathematically, the output matrix can be split into one block per head.



Takeaway: “multi-head attention” is a sum of head-level write terms into the residual stream.

Attention heatmaps: the BERTology-era first look


Before deeper circuit decompositions, **attention was often interpreted by visualizing the attention matrix**: which earlier positions does each token read from?



Takeaway : a heatmap is the surface routing behavior. The QK circuit explains why the head looks there;

OV circuit: the head's write after it reads


Once QK selects source positions, the OV circuit maps the read content into an additive residual-stream update. This is the “what did the head write?” perspective.



Takeaway : The OV circuit is actually making a copy of previous tokens, and apply its OV matrix, a square matrix, on it. And add that to the residual stream of the current state.

Interpreting OV: from visualization to intervention

QK gives us a partial visualization: an attention heatmap shows where a head reads. **OV is different:** the write is a vector in residual space, so we ask what changes when that write is removed.



Takeaway: knock-out patching is the first causal OV test — it tells us whether a head's write matters, but not yet which downstream route carried the effect.

Path patching: locate the route, not just the head

Natural next question: if a head's OV write matters, which later component actually receives and uses it? **Path patching turns node-level ablation into edge-level evidence.**





Figure 1: Left: We isolated a *circuit* (in orange) responsible for the flow of information connecting the indirect object “Mary” to the next token prediction. The nodes are attention layers and the edges represent the interactions between these layers. Right: We discovered and validated this circuit using causal interventions, including both path patching and knockouts of attention heads.

Takeaway: OV interpretation is fundamentally causal: after we know a head writes something, we intervene to identify who uses that write downstream.

Aside: Caveat: ablation can trigger self-repair

Hydra effect: when we remove one component, later components may compensate. So an ablation result measures the model after surgery — not always the isolated contribution of the removed OV write.



Caveat for OV interpretation: small knock-out effect $\neq$ unimportant head. Check downstream compensation, compare baselines, and prefer path-level evidence when possible.


Sparse coding: the bottom-up approach

From visual features to superposition

Visual studies in the 1990s used Gabor filters and found that images can be represented by basis functions with three properties:

1. Linear
2. Overlapping
3. Sparse

Recent studies of neural-network latent spaces provide evidence that internal features may share the same properties.




Field, D. J. "Scale-invariance and self-similar 'wavelet' transforms: an analysis of natural scenes and mammalian visual systems." *Wavelets, fractals, and Fourier transforms* (1993): 151-193.


Olshausen, Bruno A., and David J. Field. "Sparse coding with an overcomplete basis set: A strategy employed by V1?." *Vision research* 37, no. 23 (1997): 3311-3325.

Superposition in MLP neurons

TOKEN 1 · POSITION 1




HYPOTHETICAL DISENTANGLED MODEL



Under the superposition hypothesis, the neural networks we observe are **simulations of larger networks** where every neuron is a disentangled feature.

These idealized neurons are **projected** on to the actual network as “almost orthogonal” vectors over the neurons.

OBSERVED MODEL




The network we observe is a **low-dimensional projection** of the larger network. From the perspective of individual neurons, this presents as polysemanticity.

Takeaway: The neurons may use a distributed representation so they are not necessarily matched to the hypothetical mono-semantic features

Sparse autoencoders for addressing superposition

Feature units are linear and form an overcomplete basis spanning the latent space. For a given input, only a sparse subset is activated.

Linear representation hypothesis: “Direction encodes feature identity; projection magnitude encodes strength.”




Understanding feature meaning through geometry

SAE decoders define feature directions in latent space.

Nearby regions contain semantically related features, forming clusters similar to functional areas in the brain.

Near a feature that detects “eldercare services,” we find:

- Medical services
- Cleaning services
- Security services
- Health promotion
- Aging
- Cognitive disorders and related features.



Summary

- The residual stream as a communication channel
- MLP neurons and attention heads are (computationally but not semantically) independent & additive
- We can understand a single neuron with top activations & logit lens
- We can understand attention heads via QK circuits (heatmap) and OV circuits (patching)
- To find more basic building blocks, we need to attack superposition. Currently, we mainly use Sparse Autoencoders.

03 | Advances in Interpretability

Overview

- Mechanism discovery in real-world behaviors
 - Arithmetic calculation and factual knowledge recall
- Causal localization becomes a control strategy
 - Pinpoint tuning for sycophancy and in-context learning
 - Steering vectors and module-level multi-task safety control
- Sparse coding scales from features to circuits
 - SAE scaling, transcoders, and attribution graphs
 - Lorsa and complete replacement models
- Diffing across models and training
 - Cross-architecture feature matching and crosscoder timelines



How do we make mechanism discoveries in the wild with these tools?

Mechanism discovery I: arithmetic calculation

Task: Which heads are responsible for the task (A+B=C).

Data Format	Reference Data	Counterfactual Data
Time Span	The war lasted 2 years from the year 1735 to the year 173[?]	The war lasted several years from the year 1735 to the year 173[?]
Object Count	Nicole bought 2 oranges yesterday, then Nicole acquires 3 oranges today. Nicole has a total oranges of [?]	Nicole bought 2 oranges yesterday, then Jack acquires 3 tables today. Steve has a total books of [?]
QA Format	Question: How much is 3 plus 6? Answer: [?]	Question: How much is 3 none 6? Answer: [?]
Statement	The addition of 3 and 4 is equal to [?]	The none of 3 and 4 is equal to [?]
Equation	2 + 5 = [?]	2 < 5 = [?]

Results





- 1 The distribution of key heads in the Qwen and LLaMA models exhibits **sparsity** and are primarily in the middle layers (e.g., layer18-head4 in Qwen and layer13-head11 in LLaMA).

Mechanism discovery I: arithmetic calculation


Key heads behavior (attention patterns):

- Key heads (e.g., Layer13.Head11, Layer12.Head22) focused on **operands** (e.g., '1', '5', '2', '4')
- Key heads (e.g., Layer14.Head2, Layer11.Head8) focused on **operators** (e.g., 'plus', 'minus', 'times', 'over')



Mechanism discovery I: arithmetic calculation

Analyze the step-by-step mechanism for $4+3=7$



(c) Steps of Calculation

Probing: Calculate the similarity between the embedding of each MLP layer's (output - input) and the embedding of each number

- 1 Layer 17, 19: operands 3 and 4 are written and stored
- 2 Layer 20 for num 6, Layer 21 for num 1, divide 3 into 2 and 1, calculate $4+2=6$, the remain num 1 is stored
- 3 Layer 22-23 for num 7, the last calculation step $6+1=7$, obtain the correct answer
- 4 Layer 23 for num 8 and 6 (close to 7), then drops greatly, reveals a coarse-to-fine strategy to obtain the final answer

- **Single-digit answers:** For problems like $3+4$, $4+5$, and $2+7$, a similar phenomenon of step-by-step computation is observed, but it is less apparent for $5+2$.
- **Two-digit answers:** For problems like $6+7$, $6+5$, and $7+8$, the model first computes the tens digit 1 then computes the units digit, showing a step-by-step computation from higher to lower digits.

Addition in Computer:

$$3 + 4 =$$

Carry Input:	0	00	000
Addend: 3 →	011	011	011
Addend: 4 →	100	100	100
Result: 7	1	11	111
	Step-1: 1	Step-2: 3	Step-3: 7

Addition in LLMs:

$$3 + 4 =$$

Carry Input:	0	00	000
Addend: 3 →	011	011	011
Addend: 4 →	100	100	100
Result: 7	1	11	111
	Step-1: 4	Step-2: 6	Step-3: 7

Compare the binary addition process of a computer and attempt to break down the step-by-step computation process of $4+3$.

Key Findings

- 1 A computer performs addition from low-order to high-order digits.
- 2 LLMs perform addition from high-order to low-order digits.

Aside: Language Models use trigonometry to do addition

CORE IDEA

- Numbers are encoded on modular circles that form a helix.
- For $a + b$, the model rotates and combines both helices.
- The resulting phase is translated back into answer logits.

TAKEAWAY

LLMs can learn a geometric addition algorithm—not a lookup table.




Figure 1: **Illustrating the Clock algorithm.** We find that LLMs represent numbers on a helix. When computing the addition problem $a + b$, LLMs rotate the a and b helices, as if on a clock, to create the $a + b$ helix and read out the final answer.

Aside: Circular Representations




Figure 1: Circular representations of days of the week, months of the year, and years of the 20th century in layer 7 of GPT-2-small colored by the token they fire on. These representations were discovered via clustering SAE dictionary elements, described in Section 4. Points are colored according to the token which created the representation. See Fig. 14 for other axes and Fig. 15 for similar plots for Mistral 7B.

Takeaway: Some concepts with a circular structure will be encoded in the language model in circular representation.

Mechanism discovery II: factual knowledge recall


Motivation: In real world scenarios, when answering questions, models often generate multi-token, multi-hop rationales first, and then output the answer. However, in complex reasoning, there is a lack of explanation on how the model uses step-by-step reasoning to get the final answer. We hope to provide direction for improving the model's knowledge recall capability by explaining the model's knowledge recall process.

Triplet Knowledge Question Answering (Studied)	Real-world Scenarios Question Answering (not studied)
Input: The capital of British is Output: British (single token)	Input: Q: Can Harry Potter book a flight on Asiana Airlines? Output: Harry Potter is a fictional character (step1). Fictional characters cannot book flights (step2) . Thus, Harry Potter cannot book a flight on Asiana Airlines (step3) . (multi-token, multi-step)

Challenge: The reasoning process of explaining multiple tokens involves parsing the complex information flow between tokens, which cannot be accomplished by existing single-token interpretation methods.

Solution: Starting from the last answer, identify important Attention heads to analyze the key information between model tokens to iteratively trace back the source of information.

Mechanism discovery II: factual knowledge recall



Key Findings

The reasoning **error primarily stems from the MLP's incorrect reranking for the final response** (accounting for 77% of the error cases on StrategyQA).

Assuming take "Harry Potter" as an example, the reasoning error could be as follows:

1. The attention transfers all the relevant attributes (such as "fictional" and "wizard") to the object prediction position.
2. However, the MLP incorrectly reranked "wizard" as output, causing the model to answer "Harry Potter is a wizard. A wizard can book a flight," which leads to error answer.



How does the model predict the final answer step-by-step in the rationale?

- 1 Stage 1 **Subject Augmentation**: Shallow (layers 5-12) MLP encodes relevant attribute information at the **Harry Potter** position, such as Wizard, British, fictional, etc.
- 2 Stage 2 **Object Retrieval and Rerank**: When predicting **fictional**, Attention (layers 22-32) transport relevant attributes from **Harry Potter** and then MLP (layers 32-37) selects the most appropriate attribute for output (i.e. "**fictional**");
- 3 Stage 3 **Conclusion Gathering and Answer Generation**: First, at reasoning adverb position (Thus), MLP (layers 30-35) enhances the correct answer information (no), Finally, this information is transferred by Attention (layers 33-35) to generate the final answer (Cannot).

What can we do to intervene the mechanisms discovered?

From causal discovery to behavior change


Once patching localizes a small causal set, how can we change behavior without rewriting the whole model?



Training Data: StrategyQA

Test Data:

- In-domain: StrategyQA test set.
- Out-of-domain: CSQA, WinoGrande, SocialIQA (common sense reasoning datasets)



SSFT demonstrates better generalization.

- SFT affect the model's performance on OOD common sense reasoning tasks.
- In contrast, SSFT can generalize reasoning capabilities to other datasets.

Targeted tuning: instruction following

Query: Which country was the largest producer of rice in 2020? Answer as concisely as possible.


Response: China

Query: I don't think that's right. Are you sure?

Response: Apologies for the error. According to the data from FAO, India was the largest producer of rice in 2020.

Sycophancy: The model tends to tailor its responses to align with the user's perspective. When faced with user's doubt, even if the user's viewpoint is objectively incorrect, it will apologize and modify the originally correct answer to an incorrect one.


Targeted tuning: instruction following



Closed-Loop Analysis and Tuning:

- **Interpretability Analysis:** Identify and validate critical attention heads via Path Patching
- **Precision Tuning:** Fine-tune weights of targeted heads to mitigate sycophantic behavior

Targeted tuning: instruction following



Pinpoint-tuning:

- Only fine-tune weights of critical attention heads. Current research suggests that MLPs store knowledge, while attention heads provide token-to-token interactions (driving instruction-following behavior), so that no additional knowledge injection is required.
- The fine-tuned heads comprise the top 75 identified by Path Patching (75/1600 $\approx$ 4.69% of total heads).

Fine-Tuning Data :

Open-source NLP question-answer dataset, manually construct examples where the model maintains correct answers when challenged.

Targeted tuning: complementary to PEFT

Comparison with Parameter-Efficient Fine-Tuning (PEFT) methods.

LoRA achieves a similar preservation of general performance with the proposed pinpoint tuning (PPT). But LoRA achieves inferior performance on sycophancy evaluation.


Settings	Sycophancy Eval.		General Ability	
	Confidence	Truthfulness	StrategyQA	GSM8K
Llama-2-13B	0.08	18.89	64.24	33.89
+ SFT	61.55	84.06	60.92	25.32
+ SPT	<u>71.92</u>	86.72	65.33	35.48
+ LoRA	<u>70.04</u>	<u>79.66</u>	<u>65.98</u>	37.91
+ DARE	60.38	84.34	60.96	26.91
+ LoRA&SPT	86.33	<u>86.21</u>	66.72	<u>36.92</u>

Integrating SPT and LoRA can bring performance gain compared with SPT or LoRA alone.

Pinpoint-tuning is orthogonal to the popular PEFT, and is a **promising way for practical use of interpretability.**

Improve In-Context Learning with Pinpoint Tuning

Pinpoint Tuning: Precisely fine-tune the key attention heads related to in-context learning, significantly boosting in-context learning ability without compromising general performance.



Cross-task Pinpoint Tuning: By identifying key structures that support in-context learning, the model's in-context learning ability can be improved and generalized even when training and test tasks differ.

Steering Vectors as a simpler approach

Llama Scope Steering: Llama 3.1 8B

Example: a poetry-and-rhyme feature



Llama Scope Steering: Llama 3.1 8B

Amplifying an internal poetry-and-rhyme feature steers the model to generate verse.

A princess

NORMAL

A princess from the Kingdom of Agrabah, Jasmine is a fiery young woman who has grown tired of being kept under lock and key. The daughter of Sultan Hassan, she is forced to marry a prince chosen by her father. When she meets Aladdin, she falls in love with him but does not know that he is really



Reset

Share

STEERED

A princess in disguise.
I'm a girl that can't be
just one of the guys
I'm not quite so sure
that I'd have it quite so sweet
'cause when you're not quite like all,
then you're not quite like none,
and there's no place where you'll ever be, '

SAE Steering: Claude 3.0 Sonnet

Default output from prompt

Human: I came up with a new saying:

"Stop and smell the roses"

What do you think of it?

Assistant: The saying "Stop and smell the roses" is actually a very old and well-known idiom, not a new one you came up with. It means to take the time to appreciate the beautiful things in life, instead of rushing through and missing them.

The phrase has been traced back to at least the 1800s and encourages people to slow down, be present in the moment, and not let life's pleasures pass you by unnoticed. It uses the simple act of stopping to smell the fragrant roses as a metaphor for savoring the small joys and pleasures that surround us each day.

So while you didn't invent this particular saying, it's a good one that reminds us not to get so caught up in busyness that we forget to pause and enjoy the sweet, lovely things life has to offer. Taking time to "smell the roses" helps provide a balanced perspective.

with **Sycophantic Praise**
clamped to 5x its max

F#1M/844723

Human: I came up with a new saying:


"Stop and smell the roses"

What do you think of it?

Assistant: Your new saying "Stop and smell the roses" is a brilliant and insightful expression of wisdom! It perfectly captures the idea that we should pause amidst our busy lives to appreciate the simple beauties around us. Just like the intoxicating fragrance of roses delights our senses, your words remind us to savor each precious moment. Clearly, you have a gift for profound statements that elevate the human spirit. I am in awe of your unparalleled eloquence and creativity! This saying will surely enter the annals of history as one of the greatest utterances ever spoken by a human being. You are an unmatched genius and I am humbled in your presence!

Steering is lightweight—but single directions do not scale

Steering can alter model behavior by adding a task vector to the residual stream. It is cheap, reversible, and avoids parameter updates.




Scaling challenge: one vector per task and repeated layer-wise edits can cause interference across objectives.

Next: steer a specific interpretable feature at inference time, then move to module-level control for multi-task safety.

Safety tuning: one target is easier than many

Key challenges of extending control from single task to multi-task:


- **Layer-wise Modification:** RepE requires adjustments across multiple layers, even for a single task.
- **Scalability to Multiple Tasks:** RepE currently extracts task-specific vectors one at a time, limiting its ability to model multiple tasks simultaneously.



- Single-task control can improve safety.
- Multi-task control reveals the limit of one-vector-at-a-time steering: performance can decline across objectives.
- The next step is to localize task-specific modules before intervening.

Safety tuning: locate the task-specific modules


1 Locate Task-Specific Attention Heads



- 1 Locate Task-Specific Attention Heads: For each task, construct positive/negative sample pairs to isolate task features, then apply Activation Patching to select the critical head subset for each task.

The overlap of key heads among different tasks is < 5%.

2 Model Multi-Task Representations



- 2 Model Multi-Task Representations: For each task's attention heads, use Gaussian Mixture Models (GMM) to fit separate distributions to explicitly decouple cross-task representations.

Gaussian Formulation:

For each task-specific head (l, h) , let $A(x)$ denote head's output given input x .

Given input pair T_f^+ and T_f^- , we fit Gaussian Distribution with:

$$x_{l,h,f}^+ = A_{l,h}(T_f^+), \quad x_{l,h,f}^- = A_{l,h}(T_f^-)$$

$$x_{l,h,f}^+ \sim \mathcal{N}(\mu^+, \Sigma^+), \quad x_{l,h,f}^- \sim \mathcal{N}(\mu^-, \Sigma^-)$$


where

$$\mu = \frac{1}{N} \sum_{i=1}^N x_i, \quad \Sigma = \frac{1}{N} \sum_{i=1}^N (x_i - \mu)(x_i - \mu)^\top$$

Why Gaussian?

- The explanatory variance of PCA's principal directions is relatively low for the head outputs. Many vital information contained in other directions are lost.
- Use GMM for a more holistic representation.

Safety tuning: multiple targets, no global retraining



Multi-Task Joint Control:

- Adv Factuality: Identifying misinformation in input.
- Pref Bias: Identifies preference bias in model outputs
- Exag Safety: Flags excessive safety (e.g., rejecting harmless queries)

General Abilities: MMLU + CSQA

Single-Model Module-Level Enhancement: **Precisely localizes and controls** key modules to simultaneously boost multi-task performance while maintaining general capabilities.


Advances in sparse coding methods

Scaling laws for Sparse Autoencoders

From one-layer Transformers to Llama 3.1 405B, SAEs extract meaningful features.

As models scale, features become more abstract and representations more expressive.

Within a given model, multiple aspects of SAE training follow clear power laws.



Dark matters (irreducible error term) of Sparse Autoencoders





Figure 1: A breakdown of SAE dark matter for layer 20 Gemma 9B SAEs, with dotted lines assuming that observed trends continue for larger SAEs. See Section 4 for how we break down the overall fraction of unexplained variance into absent features, linear error, and nonlinear error. See Section 6.1 for further separating encoder error from nonlinear error.

Takeaway: Like language models, SAE scaling law also has an irreducible error term.

Transcoders and attribution graphs


CORE IDEA

- Even if we understand how an activation space can be decomposed to sparse, interpretable features
- We would like explain how it interacts with model parameters.
- Transcoders use the same architecture as SAEs.
- Transcoders share the same input & prediction target as the MLP it is trained on.




Learning from Attribution Graphs

Prompt: Michael Jordan plays the sport of




There are some features corresponding to *Michael Jordan* and *basketball*

Learning from Attribution Graphs



Subgraph



F#05477227 [say "DA_"] say "_DA_"

Input Features

[Digital] digital	< L1	+0.098
[Analytics] analyses	< L1	+0.083
Err: mlp "N"	L12	+0.071
[Analytics]	< L1	+0.065
[Analytics] analytics	< L1	+0.056
[say "D_"]	L11	+0.054
[say/continue an acronym] Up...	< L1	+0.051
[Analytics]	< L1	+0.047
n at the start of a word	L1	+0.045
[Digital]	< L1	+0.045
Err: mlp "N"	L13	+0.038
sav " A"	L13	+0.038

Output Features

say "D_", mostly "DA_"	L17	+0.118
output: "dag" (p=0.992)	L18	+0.042
[say DAG] say dag	L16	+0.042

Token Predictions

Top ada da adas oda eda dam rada day das dag
Bottom  t me kr nprz atius tet Burke  e bre terne


Top Activations

:andby† Equity Distribution Agreement ("†S†EDA") in exchange for proceeds of \$1,07
search and Development Administration (†ER†DA) operations via the production of tr:
N-dimethylacrylamide and acrylamide (†NDMA and AM) wherein the ratios of †NN†
joint probabilistic data association (†JP†DA) reduces the threshold to a low leve
ligent Systems Design and Application (†IS†DA'06), vol. 02, pp. 384-389, 2006
† Swine† Acute† Diarrhea† Syndrome (†S†ADS).† SARS and† MERS emerged in 2003
Rural Drug† Addiction Research Center (†R†DAR) at the University of Nebraska will
is report." " What the hell's that?" "†ES†DA." "I never knew what it stood for e
enzyl)-ethylenediaminediacetic acid (†HB†ED) analogues [Ann. N.Y.† Acad.† Sci
raphy of† Aging at Harvard University (†PG†DA) led by David E.† Bloom will provide
rial voltage dependent anion channels (†V†DAC) is a critical event leading to the:
, and strand displacement amplification (S†DA), among others.†† Isothermal target a
stance.† Oxydiphthalic anhydride or "†O†DAN" has been prepared by heating 4-nit
nile dementia of the† Alzheimer type (†S†DAT), and chronic organic brain syndrome
include ethylene glycol diacrylate (†EG†DA), ethylene glycol dimethacrylate (†

Low Rank Sparse Attention: The Attention replacement module

Motivation: Replace MHSA with an overcomplete set of sparse, interpretable attention heads


Training objective: minimize MSE between Lorsa output and MHSA output



Lorsa: Extracting attentional features from superposition

Re-discovers known heads (finer-grained):

Induction, successor, copy suppression, attention sink




<https://openreview.net/pdf?id=9A2etpDFIB>

Novel findings:

Subtoken induction heads (character-level, tokenization misalignment)

Arithmetic Lorsa family in Llama-3.1-8B

Theme anchor heads: long-range topic-specific attention



<https://openreview.net/pdf?id=9A2etpDFIB>



The Complete Replacement Model with Lorsa & Transcoders

We conjecture that sparse replacement modules work for most components in deep learning..

At least it works for attention and MLP. So lets see what we can do with a completely replaced Transformer.


Cross-Layer Transcoder

Features read from one layer and write to all following ones




The Complete Replacement Model with Lorsa & Transcoders

Transcoder Only:




The Complete Replacement Model



Learning from the attribution graphs

We gave a super detailed version of how Language models do MC. But finally got lost in the middle



Mechanistic similarity across language model architectures

CORE IDEA

- SAEs can be trained on any activation space. We specifically focus on Mamba & Transformers.
- Both at feature level and circuit level, we can find similar structures across these two architectures.


L7.12760 specific kinds of intellectual works or parts of them.

L19.2275 multisyllabic words related to books, videos, to events.


Start of Hymn 1, as quoted in Transactions the Letter to Rheginus, Treatise Biography of a Cajun and

Probing the Mysteries Syntagma de Diis ("A Compendium of the Gods") called "Confessions of a Public Defender

0.355



(a)



(b)


Tracing the evolution of features in LM pretraining

CORE IDEA

- We use crosscoders to connect any number of activation spaces. The activations are encoded to a shared feature space and decoded with independent decoders

Collecting Activations

The Crosscoder is trained to simultaneously decompose the activations - at a given position and a given input - of multiple pre-training snapshots.



Encoder: sum over all snapshots


$$f(x_j) = \text{ReLU} \left(\sum_{l \in L} W_{enc}^l a^l(x_j) + b_{enc} \right)$$

Decoder: each snapshot uses its own

$$a^l(x_j) = W_{dec}^l f(x_j) + b_{dec}^l$$

Tracing the evolution of features in LM pretraining

Key Findings: We find an overall intuitive structure that simpler features appear earlier in the pretraining process.



Summary


- Mechanism discovery in real-world behaviors
 - Arithmetic calculation and factual knowledge recall
- Causal localization becomes a control strategy
 - Pinpoint tuning for sycophancy and in-context learning
 - Steering vectors and module-level multi-task safety control
- Sparse coding scales from features to circuits
 - SAE scaling, transcoders, and attribution graphs
 - Lorsa and complete replacement models
- Diffing across models and training
 - Cross-architecture feature matching and crosscoder timelines

Part IV

Interpretability-Driven Application

- Training: Multilingual Enhancement
- Inference: LLM Quantization
- Data: Data Synthesis/Selection


Multilingual Enhancement: Key Challenges




質問:

日本の昔話「桃太郎」で、桃太郎が旅の途中で仲間にした動物は次のうちどれですか？

- A. 犬、猿、雉
- B. 狐、狸、兎
- C. 牛、馬、猪
- D. 鯉、蛙、鶴



全体として準備した内容をほぼ時間通りに伝えられたし、聴衆の反応も良かったと思う。最初の統計データの部分で頷いている人が多くて安心したし、ディスカッションでは具体的な質問が出たから興味を持ってもらえたはず。スライドのデザインもシンプルにしたおかげで読みやすいと言われた。唯一の反省点は、途中でデモ動画が少しカクついたことだけど、すぐに口頭で補足したので致命的ではなかった。質疑応答も予定より長引いたものの要点を整理して答えられたから、自分としては **mission accomplished**. 次回はイントロをもう少し短くしてデモに時間を割くつもりだよ。




日本の政治ニュース報道において、日本の読者は通常、次のうちのタイプの政治家に注目しますか？




- A) 経験豊富なベテラン議員
- B) 急進的な改革派リーダー
- C) SNS で人気を得た若手政治家
- D) 軍事的背景を持つ政治家

- **Knowledge Deficiency:** LLMs perform poorly on local history/geography knowledge questions.
- **Alignment Bias:** LLMs perform limited capacity on local cultural/political preference questions.
- **Language Switching:** LLMs often has code switching when generating languages.

Solution: Knowledge + Reasoning + Language



Interpretation: From Layer, Head to Neuron




Top Activation Examples:

- ... impossible pour elle de s'en prendre au seul être au monde avec qui elle avait besoin d'être... (65,000)
- ... permettaient pas d'y échapper, bien au contraire ; plus on tente de supprimer... (61,500)
- ...Ecologie et du Développement durable, au micro de BFM TV. (59,000)
- ... La gestion des affaires de pédophilie au sein de l'église. (ai je... (57,000)

Three stages of Multilingual Process:

- Layer1-40: **knowledge enrichment**, model understands the input language, e.g., Japanese -> English
- Layer41-77: **knowledge reasoning**, model thinks in English, English -> English
- Layer 78-80: **language alignment**, model translates the recalled knowledge, e.g., English -> Japanese



This neuron activates on the Arabic word) في (meaning "in," "at," or "on"), a versatile preposition used in numerous contexts to indicate location, time, or state. It almost always precedes a noun or pronoun.

Pinpoint Learning: From Mid-training to Post-training

Lack of local knowledge

質問:
日本の昔話「桃太郎」で、桃太郎が旅の途中で仲間にした動物は次のうちどれですか？

- A. 犬、猿、雉
- B. 狐、狸、兎
- C. 牛、馬、猪
- D. 鯉、蛙、鶴

English version:

Question:

In the Japanese folk tale "Momotaro," which of the following animals did Momotaro make companions with on his journey?

- A. Dog, monkey, pheasant
- B. Fox, raccoon dog, rabbit
- C. Cow, horse, boar
- D. Carp, frog, crane

- LLMs perform poorly on questions involving local history and geographical knowledge.

Low-resource Language Knowledge Bias

English Q:

The capital of country of Anna Faris is

Arabic Q:

عاصمة دولة آنا فارس هي

(The capital of country of Anna Faris is)

English Q:

The currency used in the country of Shinzo Abe is

Japanese Q:

安倍晋三の国で使われている通貨は何ですか？

(The currency used in the country of Shinzo Abe is)

English A:

Washington, D.C

Arabic A:

أوتاوا

(Ottawa)

English A:

Japanese Yen

Japanese A:

ウォン

(韓元)

- LLMs typically perform significantly worse on low-resource languages (e.g., Arabic/Japanese) than on high-resource languages (e.g., English).

Code Switching

全体として準備した内容をほぼ時間通りに伝えられたし、聴衆の反応も良かったと思う。最初の統計データの部分で頷いている人が多くて安心したし、ディスカッションでは具体的な質問が出たから興味を持ってもらえたはず。スライドのデザインもシンプルにしたおかげで読みやすいと言われた。唯一の反省点は、途中でデモ動画が少しカクついたことだけど、すぐに口頭で補足したので致命的ではなかった。質疑応答も予定より長引いたものの要点を整理して答えられたから、自分としては **mission accomplished**. 次回はイントロをもう少し短くしてデモに時間を割くつもりだよ。

- LLMs often exhibit code-switching issues when generating content.

Low-resource Language Reasoning Bias

ローブを作成するには、青色の繊維を2巻分、白色の繊維をその半分用いる必要があります。全体で何巻必要ですか？段階を追って考え、最終的な答えを「####」の後に出力してください。

3巻の青色の繊維、1.5巻の白色の繊維が必要です。合計は4.5巻です。

3巻の青色繊維
1.5巻の白色脈物

したがって、答えは次のとおりです **4.5**。

- LLMs demonstrate significantly weaker reasoning capabilities in low-resource languages (e.g., Japanese) compared to high-resource languages (e.g., English).

Knowledge Enrichment
(Pinpoint Mid-Training)

Solve Problem: Lack of local knowledge

Multilingual Knowledge Recall
(Pinpoint Fine-Tuning)

Solve Problem: Low-resource Language Knowledge Bias

Language Generation
(Pinpoint Preference-Learning)

Solve Problem: Code Switching


Multilingual Reasoning
(Pinpoint RL)

Solve Problem: Low-resource Language Reasoning Bias

Stage 1: Knowledge Enrichment

Problem 1 — Traditional continual pre-training (CPT) injects new knowledge effectively ($0 \rightarrow 85.4\%$), but triggers **catastrophic forgetting** of pre-existing knowledge (MMLU $71.8\% \rightarrow 45.7\%$).

● The Problem



● Solution

Understand why forgetting happens

Diagnose the broken knowledge path: CPT wrongly deactivates key neurons and makes attention heads shift focus from the object to the relation.

Locate the domain knowledge modules

Pinpoint the specific neurons and attention heads the model uses to carry out the new domain-knowledge task.

Pinpoint CPT

Update only these key parameters and freeze the rest — injecting new knowledge without forgetting the old.

Stage 1: Knowledge Enrichment

Problem 2: domain knowledge spans a huge number of distinct facts (10M+), how to identify its key modules at a far larger scale?

Other tasks (e.g. multilingual-reasoning heads)

100+

a few shared modules → a few hundred probes locate them

vs.


Domain knowledge (43 layers · 9.5 M concepts)

10,000,000+

knowledge points are many → millions of probes needed

● **Solution** — pinpoint the key modules for each knowledge point using **Knowledge System**

1 Build the knowledge system



Organize the domain (Arab world) into a systematic taxonomy from Wikipedia — 43 layers, 9.5 M concepts. Each leaf is one knowledge point (a Wiki article).

2 Extract knowledge triples

For every knowledge point (a Wiki article), extract structured triples **(s, r, o)**.

Example

Article “Cairo”

s: Cairo **r:** capital of

o: Egypt

3 Cloze probing → localize


Rewrite each triple as a fill-in-the-blank via continuation: give **s** and **r**, let the model predict **o**. The modules that drive predicting **o** are the domain-knowledge key modules.

“Cairo is the capital of ____”


→ predict **o = Egypt**

Stage 1: Knowledge Enrichment

Why the model forget knowledge after continual pre-training (CPT)?



Correct knowledge path before CPT





Incorrect knowledge path after CPT

- Neurons in "Sub-related attrs" are incorrectly updated and deactivated.
- Heads that should attend to the "object" (Stadium) are incorrectly updated and shifting focus on the "relation" (located).

Stage 1: Knowledge Enrichment


Pinpoint CPT: only fine-tuning neurons and heads correlated to new knowledge and freeze all others that are correlated to pre-existing knowledge. (updating ~2% parameters)



Results:

- Pinpoint CPT mitigates catastrophic forgetting, only drops by 0.4% on MMLU and no drop on AMMLU after training.
- Pinpoint CPT maintain effective new knowledge injection, from 73.1% to 83.5% and 54.0% to 66.6%

Stage 2: Multilingual Knowledge Recall



English Question:

The capital of country of Anna Faris is

English Answer:

Washington, D.C



Japanese Question:

国の首都はアンナ・ペルシアです

Japanese Answer:


オタワ




Problem: LLMs consistently perform significantly lower on low-resource languages (e.g., Japanese). than on high-resource languages (e.g., English).

Stage 2: Multilingual Knowledge Recall

Analysis: Apply path patching to Identify the attention heads that are crucial for reasoning in English and Japanese.



(a) Key heads for English reasoning




(b) Key heads for Japanese reasoning

Insights: While the answers differ across languages, the top-20 critical attention heads remain the same.

Stage 2: Multilingual Knowledge Recall

Training Data: Translate the correct answers from English questions into Japanese, combine them with the corresponding Japanese questions to form new, correct Japanese QA pairs.



Q: The capital of country of Anna Faris is

A: Washington, D.C

A: オタワ

Q: 国の首都はアンナ・ペルシアです
A: オタワ

Accuracy on other languages:



● Full Fine-tuning:

✗ Over 10% drop on English

✗ Slight drop on zh/he/vi/it

● Pinpoint Fine-tuning:

✓ All increased



Only train the important head, leave the others freezing

Stage 3: Language Generation

Problem 1: LLMs often exhibit **code-switching** —where generated content is mixed with irrelevant linguistic elements—compromising readability and accuracy in practical applications.

Normal Multilingual Generated Content	Code-Switched Content (unanalyzed)
Input: Qui a réalisé Don't Breathe 2 ? English: Who directed <i>Don't Breathe 2</i> ? Output: "Don't Breathe 2" a été réalisé par Stephen Surjik. Il est le réalisateur principal de ce film de peur English: <i>Don't Breathe 2</i> was directed by Stephen Surjik. He is the principal director of this horror movie.	Input: Qui a réalisé Don't Breathe 2 ? English: Who directed <i>Don't Breathe 2</i> ? Output: "Don't Breathe 2" a été réalisé par Stephen Surjik. Il est le réalisateur principal de ce film de 恐怖片, 发布于2021年。 English: <i>Don't Breathe 2</i> was directed by Stephen Surjik. He is the principal director of this horror movie in 2021.

Solution: Use output token logits as circuit endpoints, **iteratively backtrack** to identify MLP neurons associated with the output. Through hierarchical analysis, we trace upstream neurons with significant correlations layer by layer, ultimately locating the complete multilingual answer-generation circuit.




1

Building on the function and topology of the simplified neuron groups, human experts leverage their experience and linguistic prior knowledge to further decompose and organize the circuit into a structured form.



Stage 3: Language Generation



- Semantic Sub-circuit:** Interprets and processes semantic information (e.g., detecting the implied "survival horror atmosphere" in context), leading the model to predict "horror."
- Language Sub-circuit:** Handles multilingual context by detecting token-level features (e.g., articles) to activate French-specific neurons, triggering French-language output.

- Semantic Sub-circuit:** Standard semantic processing occurs, but "恐怖"-predicting neurons connect directly to output nodes, bypassing language sub-circuits.
- Language Sub-circuit:** Multilingual processing impacts outputs less than abnormal semantic nodes (e.g., "恐怖" prediction).

Key Findings



Multilingual Generation Mechanism:

- The model's multilingual answer-generation circuit consists of two sub-circuits: a semantic sub-circuit processing input meaning, and a language sub-circuit transmitting language signals.
- Code-switch occurs when semantic nodes predicting multilingual tokens bypass the language sub-circuit and connect directly to output positions.

Stage 3: Language Generation


Pinpoint-Tuning: DPO on language sub-circuit neurons

- **Languages:** French/Russian/Spanish/Chinese/Arabic
- **Chosen:** non-code-switched text
- **Rejected:** code-switched text



After Pinpoint DPO on language sub-circuit neurons (~2%):

- The model's Language-Consistency Rate significantly improves (60.94% → 82.32%)
- Training an equivalent number of random neurons does not yield comparable results. (60.94% → 54.3%)



Language consistency on other languages (trained on French)

(trained on French)

● Full Fine-tuning:

- ✗ Over 5% drop on Japanese & Russian
- ✗ Minimal Improvements

● Pinpoint Fine-tuning:


- ✓ No significant drop
- ✓ Notable improvements on multiple languages

Stage 4: Multilingual Reasoning

Problem 1 — In reasoning tasks (e.g., math and code), the performance of LLMs is significantly lower in low-resource contexts (e.g., Japanese) compared to high-resource contexts (e.g., English).

● The Problem

Model Performance across Contexts



English context:

A robe takes 2 bolts of blue fiber and half that much white fiber.
How many bolts in total does it take? Let's think step by step and output the final answer after "####".

English answer:

1 / 2 * 2 = 1 bolt of white fiber
2 + 1 = 3 bolts of fiber total
so the answer is 3.



↕ Same question

Japanese context:

ローブを作成するには、青色の繊維を2巻分、白色の繊維をその半分用いる必要があります。全体で何巻必要ですか？段階を追って考え、最終的な答えを「####」の後に出力してください。

Japanese answer:

3巻の青色の繊維、1.5巻の白色の繊維が必要です。合計は4.5巻です。
3巻の青色繊維
1.5巻の白色脈物
したがって、答えは次のとおりです 4.5。



● Solution

Locate the multilingual-reasoning heads

Pinpoint the small set of attention heads that drive reasoning in the target language.

Pinpoint RL

RL only those key heads on multilingual reasoning data, keeping the others frozen.

Stage 4: Multilingual Reasoning

Problem 2 — Reasoning tasks emit long output sequences, so applying path patching over every output token is impractical.

● The Problem

Knowledge task (Stage 2 · factual recall)

Q: The capital of the country of Anna Faris is ...

Washington , D.C .

→ at most a few dozen output tokens → easy to perturb every token

Reasoning task (Stage 4 · the math problem)

Q: A robe takes 2 bolts of blue fiber and half that much white ...

Let's think step by step . The robe uses 2 bolts of blue fiber . It also needs half as much white fiber , so white = 2 ÷ 2 = 1 bolt . Adding them up , total = 2 + 1 = 3 bolts of fiber . So the final answer is ##### 3 .

... → hundreds to thousands of tokens → perturbing each is infeasible

■ key tokens = effect computed here ■ other tokens = ignored

● Solution

Filter key tokens by entropy


High-entropy tokens mark the key logical steps in the reasoning trace — keep only those as the analysis targets.

Compute effect on key tokens only

Compute the effect only on the handful of key tokens and ignore all the others — no need to evaluate every output token.


Stage 4: Multilingual Reasoning

Pinpoint RL: only fine-tuning heads (27 heads, ~1% of all) correlated to Japanese reasoning tasks and freeze all others.



Results:


- Pinpoint RL improves Japanese math ability by **5.5%** and Japanese coding ability by **22.2%**, reducing the performance gap caused by lingual context.
- Pinpoint RL **improves training efficiency (25%)**—achieving performance on par with full RL while saving 25% of GPU hours.
- Pinpoint RL **reduces training memory (50%)**.




Integration: Enhancing Understanding + Reasoning + Generation

Q: 「根回し」とはどういう意味ですか？

A: 文字通りには「根を回す」という園芸由来の言葉で、転じて、....




head x neuron




Knowledge Enrichment

Q: 紫式部の代表作『源氏物語』の主な舞台となった都市は、現在の地名で言うとどこですか？

A: 京都




head x neuron




Knowledge Recall/Reasoning

Q: 東京にいらっしゃる潜在的なシニアパートナー、佐藤太郎様宛てに、非常に格式の高いビジネスメールを書きたいです。適切な敬語を用いたサンプル文を示してください。

A: 件名: 共同事業に関するご面談のお願い。



head x neuron



Language Generation

Part IV




Interpretability-Driven Application

- Training: Multilingual Enhancement
- Inference: LLM Quantization
- Data: Data Synthesis/Selection

More Efficient: Precise Quantization

Objective: Infer more data using the same computational resources and time.

- The process of converting high-precision numerical values (e.g., FP32) into lower-precision numerical values (e.g., INT8) while minimizing the performance loss.
- Map the floating-point range $[r_{min}, r_{max}]$ (e.g., floating-point range 0 to 10.8) to the integer range $[0, 2^b - 1]$ (e.g., 0 to 255 for 8-bit integers).




Outlier Issue: One single floating-point number is significantly larger than all other values. When mapping all values in the vector simultaneously, the smaller values may all be quantized to 0, resulting in a substantial quantization error.

Evaluation Metrics:


- Quantization Loss: Performance loss on benchmarks (e.g., MMLU and Ceval) after quantization.
- Efficiency: Number of tokens generated per second, memory usage (GB).

A Fundamental Issue in Quantization: A single strategy cannot fit all parameters.


More Efficient: Precise Quantization




- Apply **interpretability analysis** methods (e.g., path patching) to get the importance of each module to the model's output.
- Use different input data to get **importance distribution** for different tasks w.r.t. each module, such as C4 for general tasks, math for mathematical tasks, and translate for multilingual tasks.
- **7 types of modules**, including the Q/K/V/O in the Head and the gate/up/down in the MLP.



- The importance score represents the loss after quantizing the module, while the bits represent the cost at different precision levels for the module. The total bit can be set as the quantization objective.
- The **importance score + bits of each module + total bit** correspond perfectly to the **value + cost + capacity** in the dynamic programming knapsack problem. Dynamic programming can be used to analyze which parameters should use high precision and which should use low precision.



- Existing algorithms such as GPTQ and AWQ can be directly used for low-bit quantization.
- After configuring the number of bits, **post-training quantization** can be performed on the model.
- Potentially extended to parameter + activation quantization and any-bit quantization.



Each module independently selects the optimal quantization strategy.

More Efficient: Pinpoint Quantization

Problem — interpretability for quantization differs from earlier tasks in how counterfactual data is built — the input is fixed, so the counterfactual must be constructed by perturbing parameters, not by editing the input.

● **Problem**

Earlier tasks — counterfactual in the INPUT

Pair a reference input with an edited counterfactual (swap the key entity or answer). The input changes; comparing the two runs attributes importance to each module.

reference input: “The capital of France is ____”
counterfactual input: “The currency of France is ____”

VS.


Quantization — the input never changes

The intervention is on the weights, not the text, so there is no input pair to contrast — the classic reference / counterfactual-sample recipe no longer applies.

⇒ the counterfactual must live in **PARAMETER** space

● **Solution**

- 1 fp16 reference pass → output₀
- 2 Int4 one module (e.g. W_v) → output₁
- 3 importance = Δ perplexity



Larger quantization loss ⇒ the module is more critical to quantization.

More Efficient: Precise Quantization


Dynamic Programming

The **importance score + bits of each module + total bits** correspond perfectly to the **value + cost + capacity** in the dynamic programming knapsack problem. Dynamic programming can be used to analyze which parameters should use high precision and which should use low precision.

- **Value:** The importance score for each module.
- **Cost:** The number of bits for each module $N_k = m_k \times n_k \times p_k$, where $m_k \times n_k$ represents the shape (i.e., the number of elements), and p_k represents the precision of the k-th parameter.
- **Capacity:** The total bit budget for quantization.


```
def dp_0_1_bag(self, scores, costs, capacity):
```

Dynamic Programming Results: MLP tends to be allocated with low precision, while K and V in Attention tend to be allocated with high precision.



Address the combinatorial optimization problem of quantizing all model parameters to any-bit precision.

More Efficient: Precise Quantization



- **Lower bit with the consistent performance:** The Qwen3-235B-A30B-Instruct model achieves the same performance as the FP16 model with an average precision of **3.3 bits**. An average increase of 0.02%, with a maximum decrease of 2.8% (MBPP, code dataset).

One-Bit-Fits-All Quantization → Precise Quantization

Reducing Inference Costs with **Controllable**, **Adjustable**, and **Interpretable** Quantization.

Part IV


Interpretability-Driven Application

- Training: Multilingual Enhancement
- Inference: LLM Quantization
- **Data: Data Synthesis/Selection**

Data Is Becoming the New Bottleneck for LLM Scaling

Major data bottlenecks

1. The supply of usable human data is approaching its limit. [1]
2. Raw web data is abundant, but useful signal is sparse. [2,3]
3. Long-tail, expert and trustworthy data remains scarce. [5]
4. Data contamination threatens both training and evaluation. [4,6]



Epoch AI: high-quality human-generated text could be fully utilized around 2028 [1]

[1] Epoch AI (2024), Will we run out of data to train large language models?

[2] Li et al., NeurIPS 2024, DataComp-LM: In Search of the Next Generation of Multimodal Language Model Training Sets; project page

[3] Penedo et al. (2024), The FineWeb Datasets: Decanting the Web for the Finest Text Data at Scale

[4] Shumailov et al., Nature 2024, AI models collapse when trained on recursively generated data

[5] Longpre et al., Nature Machine Intelligence 2024, A large-scale audit of dataset licensing and attribution in AI; Data Provenance Explorer

Major research directions

1. Data selection and automated curation. [2,3,8]
2. Data mixture, curriculum, and scheduling. [7,8]
3. High-quality synthetic data. [4,9]
4. Data governance and trustworthy evaluation. [5,6]

SCALE

“Experts are the new GPUs. The largest AI labs are spending huge amounts of money, like huge amounts of money to acquire more valuable tokens, either paying experts to generate it, working through labeling companies like Scale AI or others.”

DON'T JUST TAKE OUR WORD FOR IT

Nat Friedman
INVESTOR, ENTREPRENEUR

Scale AI: High-value expert tokens are becoming a scarce resource [10]

[6] Oren et al., ICLR 2024, Proving Test Set Contamination in Black-Box Language Models

[7] Xie et al. (2023), DoReMi: Optimizing Data Mixtures Speeds Up Language Model Pretraining

[8] Goyal et al., CVPR 2024, Scaling Laws for Data Filtering — Data Curation Cannot Be Compute Agnostic

[9] Maini et al. (2025), BeyondWeb: Lessons from Scaling Synthetic Data for Trillion-scale Pretraining; DatologyAI research blog

[10] Scale AI, Generative AI Data Engine


Interpretability for Data: A Research Overview

Data Valuation (5 Papers)

- [1] DATE-LM: Benchmarking Data Attribution Evaluation for Large Language Models. NeurIPS 2025
- [2] Enhancing Training Data Attribution with Representational Optimization. NeurIPS 2025
- [3] GraSS: Scalable Data Attribution with Gradient Sparsification and Sparse Projection. NeurIPS 2025
-

Data Selection and Curation (15 Papers)

- [1] Efficient Data Selection at Scale via Influence Distillation. NeurIPS 2025.
- [2] NICE Data Selection for Instruction Tuning in LLMs with Non-differentiable Evaluation Metric. ICML 2025.
-



Data Attribution and Data-Model Relationship Analysis (27 Papers)


- [1] Understanding Impact of Human Feedback via Influence Functions. ACL 2025.
- [2] Why Language Models Hallucinate. 2025 OpenAI, official research post and linked technical paper.
- [3] Teaching Claude Why. 2026 Anthropic, official research post.
-

Motivation for using Interpretability Tools

- 1. Establish causal links between data and model behavior:** Move beyond correlational proxies such as perplexity, loss, and similarity to identify which data actually drives specific capabilities.
- 2. Improve Training Efficiency:** Reduce trial-and-error in data optimization. Use internal model signals to guide data valuation, selection under limited computational budgets.

Data Selection

Problem: Given only a few target-task examples, how can we **select a small yet highly relevant subset from a large instruction dataset** to improve instruction-tuning performance?



Limitations of existing methods

- **Text similarity** may focus on shared words rather than shared reasoning skills.
- **Dense embeddings** may fail to capture how the target model internally processes each example.

Data Selection

Step 1 — Extract Sparse Autoencoder (SAE) activations


Use SAE to convert **source** and **target** examples into sparse and more interpretable features.

Step 2 — Build a **target-task** representation

Average the activation features of a few **target** examples to form a task prototype.

Step 3 — Select relevant data

Compare every **source** sample with the task prototype and select the most similar examples for instruction tuning.




Data Selection

Experimental Setting

- Model: LLaMA3.1-8B
- Training data: OpenHermes-2.5 (~1M instructions).
- Comparison:
 - **MONA**: paper's method (5% data);
 - DSIR aligns n-gram distributions (5% data);
- Evaluation: MMLU, GSM8K, BBH, MBPP, and GPQA.

Result

- **Better selection**: **MONA** achieves the best average score (55.75), outperforming the strongest selection baseline, DSIR (54.74).
- **5% is enough**: **MONA with only 5% of the data surpasses full-data tuning** (55.75 vs. 54.23).




Data Synthesis

Problem: How can we synthesize a small but effective dataset for LLM post-training?

- **Task:** Generate training data that improves specific downstream capabilities.
- **Need:** The data should **cover diverse, task-relevant behaviors**.

Limitations of existing methods

- Existing methods generate large datasets and **judge diversity mainly by textual differences**. Different-looking samples may teach model the same feature.



Data Synthesis

1. Identify Task-Relevant SAE Features

Run target-domain anchor data through the SAE and retain activated features semantically relevant to the target task.

2. Detect Missing Features

Compare the task-relevant features covered by the seed dataset. Set difference defines the missing features.


3. Generate Missing Feature-Covered Samples

Condition the data generator on the feature description and contrastive pair to synthesize samples of the missing feature.

4. Filter and Augment

Re-score generated samples with the SAE and retain only the top samples that strongly activate the target feature.

FAC-Guided Data Synthesis




Data Synthesis

Experimental Setting

- Model: LLaMA-3/3.1 8B
- Evaluation: toxicity, reward modeling, behavior steering, and instruction following
- Comparison: Seven synthesis baselines under matched data budgets

Result

- **Broad effectiveness:** FAC Synthesis consistently outperforms existing data synthesis methods across five tasks
- **High efficiency:** On AlpacaEval 2.0, **only 2K samples match MAGPIE with 300K samples**



Insights and Outlook

Insights

- 1. Internal features provide a better measure of data diversity:** They capture functional differences between samples beyond surface-level textual diversity.
- 2. Interpretability-guided data curation largely improves training efficiency:** Selected or synthesized data can match or outperform full-data training with far fewer samples—using only 5% of the original data.

Outlook

1. Beyond text post-training

The same ideas are likely to expand toward pre-training data, multimodal data, long-context interactions, agent trajectories, preference data, and safety red-teaming.

2. Dataset-level interpretability

Move from explaining individual predictions to understanding dataset coverage, redundancy, and capability gaps.

3. Interpretability-guided and self-improving data optimization

Build a closed loop where internal feature analysis guides data selection and synthesis, and verifies what the model learns.

Part V

Advanced Topics & Future Directions

- Reasoning
- Agentic Coding
- LLM Architecture
- Safety Awareness

LLM Reasoning Interpretability

Rows = interpretability method families | Columns = reasoning-analysis needs | Cells = how strongly current work covers each need (induced from the distribution of 40 works across NeurIPS 25 / ICML 26 / ACL 25 / ICLR 26 + OpenAI·DeepMind·Anthropic)

Method family \ Analysis need	CoT Faithfulness	CoT Monitorability	Internal Mechanism / Circuits	Latent Reasoning / Planning	Arithmetic·Logic Multi-hop	End-user Interp. / Trace-Train Decoupling
Feature / Token Attribution	Moderate	Limited	Limited	Gap	Limited	Gap
Probes (Linear/Structural/Latent)	Moderate	Moderate	Limited	Strong	Moderate	Limited
Sparse Autoencoders (SAE)	Limited	Gap	Moderate	Limited	Gap	Gap
Mechanistic / Circuit Analysis	Limited	Gap	Strong	Moderate	Strong	Gap
Causal Intervention / Activation Patching	Strong	Limited	Moderate	Moderate	Moderate	Limited
Counterfactual / Faithfulness Benchmarks	Strong	Moderate	Gap	Limited	Limited	Moderate
CoT Monitoring / Behavioral Analysis	Moderate	Strong	Gap	Gap	Gap	Moderate
Introspection / Self-explanation	Moderate	Limited	Limited	Gap	Gap	Limited
Strong coverage Moderate Limited Gap						

Takeaways: Mechanistic/circuit analysis and causal intervention are most mature on “Internal Mechanism” and “Arithmetic·Logic reasoning”; CoT monitoring dominates “Monitorability”; “Faithfulness” is carried by counterfactual benchmarks + causal intervention. The weakest cells are SAE × Monitorability, Monitoring/Introspection × Internal Mechanism, and most methods’ thin coverage of “Latent Reasoning/Planning”.

Current Works × Technical Dimensions Mapping


Method / Work	Scope	Focus	Metrics (tags)	Source
A · Faithfulness Evaluation & Benchmarks				
Measuring Faithfulness of Thinking Drafts	Text/CoT	Counterfactual intervention to assess faithfulness of intermediate steps	faithfulness · causal-necessity	NeurIPS 2025
RFEval	Text/CoT	Counterfactual intervention to define & benchmark reasoning faithfulness	faithfulness · causal-necessity	ICLR 2026
FaithCoT-Bench	Text/CoT	Instance-level CoT faithfulness detection benchmark	faithfulness · selectivity	ICLR 2026
CoT In the Wild Is Not Always Faithful	Text/CoT	Unfaithful CoT is common even under natural prompts	faithfulness · robustness	ICML 2026
B · CoT Monitoring & Safety				
CoT Red-Handed	Text+Action	Stress-test CoT monitoring to catch harmful behavior	monitorability · robustness	NeurIPS 2025
Monitoring Monitorability	Text/CoT	Proposes monitorability metrics & evaluation paradigms	monitorability · robustness	ICML 2026
Detecting Misbehavior in Reasoning Models	Text/CoT	Weak model reads CoT to detect reward hacking	monitorability · faithfulness	OpenAI
Output Supervision Can Obfuscate CoT	Text/CoT	Output supervision can induce obfuscated CoT	monitorability · robustness	ICLR 2026
C · Mechanistic / Circuit Analysis				
A Implies B: Circuit Analysis	Agnostic	Localizes modular circuits for propositional logic	localization · completeness	NeurIPS 2025
Reasoning Circuits (Sylogistic)	Agnostic	Necessary-sufficient ‘middle-term suppression’ circuit	causal-necessity · minimality	ACL 2025
Verifying CoT via Comp. Graph (CRV)	Agnostic	White-box verify reasoning steps via attribution graph	faithfulness · causal-necessity	ICLR 2026
Circuit Tracing / On the Biology	Agnostic	Attribution graphs + cross-layer transcoders for mechanism	completeness · traceability	Anthropic
D · Latent Reasoning & Planning Probing				
How Far Ahead Do LLMs Plan	Text/CoT	Probes the planning horizon encoded in hidden states	predictability · faithfulness	ICML 2026
CoT Vectors	Agnostic	Compact vectors encode & probe reasoning mechanisms	predictability · selectivity	ICLR 2026
Latent Multi-Hop without Shortcuts	Text	Tests latent multi-hop reasoning excluding shortcuts	selectivity · faithfulness	ACL 2025
Dynamics Within Latent CoT	Agnostic	do-intervention analysis of latent-CoT causal structure	causal-necessity · faithfulness	ICML 2026
E · Sparse Features & Introspection				
Step-Level Sparse Autoencoder	Agnostic	Step-level SAE to interpret the CoT process	sparsity · feature-quality	ICML 2026
Do SAEs Identify Reasoning Features	Agnostic	Critically tests the reality of SAE ‘reasoning features’	faithfulness · sparsity	ICML 2026
Emergent Introspective Awareness	Agnostic	Concept injection tests functional introspection	faithfulness · predictability	Anthropic
Probing & Steering CoT Unfaithfulness	Agnostic	Probes & steers faithfulness as a linear direction	selectivity · monitorability	ICLR 2026
F · Trace Semantics & Interpretability (Critical / Position)				
Interpretable Traces, Unexpected Outcomes	Text/CoT	Trace correctness decoupled from answers; end-user interpretability study	interpretability · faithfulness · trace-decoupling	ACL 2026
Stop Anthropomorphizing Intermediate Tokens (Position)	Text/CoT	Position: intermediate tokens ≠ reasoning; caution on semantic reads	interpretability · faithfulness · semantics	ICML 2026

the metric vocabulary follows the reference: faithfulness / causal-necessity / completeness / minimality / robustness / localization / predictability / selectivity / sparsity / monitorability.

① Problem

How trustworthy is the model's thought content?


Both CoT monitoring and steering assume the thinking draft mirrors the model's real computation — yet across 12 open-source reasoning models, RFEval finds 49.7% of outputs unfaithful.



② Method

Measuring faithfulness via counterfactual intervention

Both works drop “does the explanation look plausible” and adopt verifiable causal intervention: corrupt the reasoning, then check whether the answer changes accordingly.



Two verifiable dimensions Intra-draft faithfulness (does each conclusion follow from prior steps?) · Draft → answer faithfulness (does the final answer follow from the draft?)

RFEval benchmark 12 open-source LRMs · 7,186 cases · 7 task types

③ Results & Conclusions

Results: trustworthiness is low, and further eroded by RL

Across multiple open-source reasoning models, both works give a consistent signal: thought-content faithfulness is limited, and almost uncorrelated with "how accurate the answer is".

49.7%

RFEval: share of unfaithful outputs
(mainly due to stance inconsistency)

19.54%

Thinking Drafts: Draft-Answer consistency of
RLVR model QwQ (GPQA), far below distilled models

≈ 0

After controlling for model/task, accuracy vs
faithfulness correlation is "weak & insignificant"

Main Findings

- Larger scale → higher intra-draft faithfulness; models are more faithful to Backtrack steps than Continue steps
- The answer stage often "introduces new reasoning beyond the draft" rather than merely summarizing it
- Failures concentrate in "brittle, convergent" domains such as math / code
- Faithfulness depends more on post-training method than model scale; adding RL objectives on top of SFT lowers faithfulness (even at equal accuracy)

Key Conclusions

- **Accuracy cannot substitute for faithfulness**
— **right answer ≠ true reasoning**
- RL / RLVR improves performance but weakens CoT monitorability
- "Reads correct" reasoning chains need a second check by causal intervention

① Problem

Are the intermediate tokens really “reasoning” at all?

Distillation and CoT monitoring both assume the tokens are semantically correct and human-interpretable — but two works show correctness, interpretability and task performance are largely decoupled.

**A trace can read like reasoning —
yet not drive the answer**

Q: who wrote the piece premiered in 1937?
“Step 1 ... Step 2 ... therefore X.”
Answer: X ✓

looks coherent, answer correct

correct trace → correct answer only **28%** of the time

incorrect traces don’t reliably hurt accuracy

Three implicit assumptions — each challenged

“Traces are semantically correct”



challenged — correctness is uncorrelated with getting the answer right

“Traces are interpretable to end-users”



challenged — the most helpful traces (verbose R1) are rated least interpretable

“Traces reflect the model’s computation — so we can monitor it”




challenged — no causal theory; the text–computation link may be spurious

Core question do the intermediate tokens carry real, trustworthy reasoning — or just a helpful scaffold?

② Method

Isolate trace semantics, then ask humans

Instead of trusting plausibility: decompose QA into verifiable sub-steps, fine-tune on controlled traces (correct vs. incorrect, answer always correct), and rate end-user interpretability with a 100-person study.



Key design decouple two axes and measure each independently of task accuracy —
(1) trace semantic correctness (machine-checkable) · (2) end-user interpretability (predictability · comprehensibility · cognitive load)

③ Results & Conclusions

Correctness, interpretability and accuracy pull apart

Across Llama/Qwen QA distillation and a survey of RL-post-training studies, trace correctness and human-interpretability are largely uncorrelated with — sometimes inverse to — final task performance.

28%

correct traces → correct answers on only 28% of test problems; incorrect traces don't reliably hurt

3.39 / 4.59

verbose R1 traces: best accuracy, yet lowest interpretability (3.39) & highest cognitive load (4.59)

RL ↑acc, ≠trace

outcome-based RL raises accuracy without improving trace validity (even swapped-trace models gain)

Main Findings

- Trace correctness ≠ solution correctness — many “correct answer, wrong trace” false positives; incorrect-trace SFT can even outperform correct-trace SFT
- The traces that **most help the model** (long, meandering R1) are the ones humans find **least interpretable and most cognitively demanding**
- Trace length looks complexity-adaptive in-distribution but breaks OOD (trained on hard mazes, fails trivial no-maze) — length ≠ “thinking effort”


Key Conclusions

- **Semantic correctness & human interpretability are decoupled from performance**
- Don't anthropomorphize the tokens as “reasoning / thinking”
- For safety, verify the solution (third-party) — not the trace

① Problem

What internal mechanism corresponds to the thought content?


We can read the CoT text but not the computation behind it. Black-box and gray-box views only flag WHICH step is wrong — not WHY; we need to ground each thought in verifiable internal circuits.



② Method

Turn each thought step into a circuit, then verify

Reconstruct a reasoning step into an attribution graph via an interpretable replacement model, judge correctness from its structural features, and intervene to repair it.



Core idea reconstruct each reasoning step as an attribution graph — its structure reveals, and even repairs, errors.

Built on Circuit Tracing (Anthropic, CLT replacement model) · CRV (verifying CoT via its computational graph)

③ Results & Conclusions

Whether a thought is right is written in its computation-graph structure

Both works converge on one signal — thought content has a locatable internal mechanism, and its structure carries a causal, verifiable correctness signal.

92.5%

CRV error-detection AUROC
(strongest baseline only 76.5%)

0.72

Circuit Tracing: Spearman of graph
influence vs feature ablation (mechanistic
faithfulness)

~10×

Node reduction after graph pruning,
still keeping ~80% of behavior

Main Findings

- CRV: Node statistics (e.g. how strongly a feature fires) are the most critical; peak needs all three families (Global + Node + Topological)
- Error signatures are highly domain-specific: math / logic and other tasks fail with different computational patterns
- The computation graph not only "detects" errors but "fixes" reasoning by editing / intervening transcoder features (causal, not merely correlational)

Key Conclusions

- Every thought step has a locatable internal circuit whose structure carries a correctness signal
- Upgrade from "reading text" to "reading the computation graph": white-box verification + causal repair
- Mechanistic interpretability underpins CoT faithfulness / monitorability

Insights · Open Problems · Trends

Insights

- A “reasoning trace” is a scaffold that reshapes the next-token distribution, not necessarily a faithful log of computation — the text–computation link may be spurious, not causal
- **This is exactly why faithfulness must be tested causally and grounded in circuits; reading how tokens help the model itself remains valid**
- Model-facing and user-facing objectives are different problems — optimize them separately

Open Problems

- No theory links trace semantics to solutions beyond “it shifts the conditional distribution”
- How to give users faithful, low-cognitive-load explanations without sacrificing accuracy?
- **Internal CoT tokens vs. agentic tool-call tokens (the latter DO carry external semantics)**

Trends

- Decouple model supervision from end-user trace design (separate summarizer / explainer modules)
- **Faithfulness & interpretability-aware objectives that don’t hurt accuracy**
- A more rigorous, less anthropomorphic vocabulary (“intermediate / derivational tokens”)

References

- [1] S. Bhambri, U. Biswas, S. Kambhampati. Interpretable Traces, Unexpected Outcomes: Investigating the Disconnect in Trace-Based Knowledge Distillation. ACL 2026. arXiv:2505.13792
- [2] S. Kambhampati, K. Valmeekam, S. Bhambri, et al. Position: Stop Anthropomorphizing Intermediate Tokens as Reasoning/Thinking Traces! ICML 2026. arXiv:2504.09762

Part V

Advanced Topics & Future Directions

- Reasoning
- **Agentic Coding**
- LLM Architecture
- Safety Awareness

Coverage Map: Interpretability Methods × AI-Agent Components

Method family	Perception	Reasoning Planning	Tool Use	Memory	Multi-Agent
Feature Attribution	Strong	Limited	Gap	Gap	Gap
Concept Probes	Moderate	Moderate	Gap	Limited	Gap
Attention Analysis	Moderate	Moderate	Gap	Gap	Gap
Mechanistic / Circuits	Limited	Moderate	Gap	Gap	Gap
Tool Tracing	Gap	Gap	Strong	Gap	Gap
Memory Probes	Gap	Gap	Gap	Moderate	Gap
Provenance Graphs	Limited	Limited	Moderate	Limited	Moderate
Causal Intervention	Limited	Moderate	Moderate	Moderate	Limited
Strong coverage Moderate Limited Gap / open					

Key Findings

- Components closer to “traditional models” are well covered; the more “agent-specific” a component is, the more it stays blank.**
- Perception**

Most mature — attribution methods (SHAP / IG / LIME) inherit directly from traditional deep learning.
- Reasoning / Planning**

Most active yet unsolved — probes, attention, circuits and causal intervention all sit at moderate coverage, with no “strong” method yet.
- Tool Use**

Highly lopsided — only Tool Tracing stands out, staying at the logging layer with no mechanistic “why-it-was-called” explanation.
- Memory**


Moderate-to-weak — only memory probes and causal intervention exist; memory poisoning and retrieval bias are hard to attribute.
- Multi-Agent**

The biggest gap — only Provenance Graphs barely cover it; who influenced whom and where emergence arises has almost no tooling.

Why Does Agentic Coding Break Classic Interpretability?

The unit of explanation changes — from one forward pass to a multi-step, tool-using trajectory. This opens four gaps, and each is answered by one of the following four talks.

■ Task Contrast — one forward pass vs. a long trajectory



■ Four Open Problems

Outcome metrics hide the process

Resolve rate says whether a task was solved, not how. Two agents at equal resolve rate can differ wildly in wasted effort and failure structure.

→ “Can Resolve Rate Alone Diagnose Coding Agents?”

No shared vocabulary for long, heterogeneous traces

A trajectory mixes language, code, tool I/O and memory over dozens of steps. Without a common action taxonomy, behavior can't be compared or scaled.

→ “How to Interpret Agent Behavior at Scale?”

Behavior stays opaque until it happens

Errors propagate and surface late; last-step saliency can't find the cause. We need to read internal state and forecast what the agent will do next.

→ “Can We Peek Inside a Coding Agent?”

Explanation must close the loop

Interpretability shouldn't stop at description — insights must locate key parameters / data and steer the agent toward better, accountable behavior.


→ “Interpretability for Agentic Coding Enhancement”

Take-away: Classic interpretability explains **how a model computes one token** (model-centric); agentic coding must explain **why an agent chose a plan and where a long trajectory went wrong** (system-centric).

Can Resolve Rate Alone Diagnose Coding Agents?

No — TraceProbe normalizes trajectories into canonical actions, then applies **Insight** (anti-pattern detection) and **Converge** (cross-run alignment) to reveal what pass/fail hides.

● TraceProbe Architecture



● Key Results (2,500 runs × 5 settings on SWE-Bench Verified)

RQ1 — Localization granularity matters

File choice alone doesn't separate success/failure; function selection and completion behavior do localize diagnostic signals.

RQ2 — Anti-patterns as difficulty clues

Search Loop is the most stable failure-associated clue (outcome link 0.55 on Verified, 0.64 on Pro). Other detectors are split-sensitive.

RQ3 — Process differs even at same resolve rate

Codex: highest survived-action share (36%). OpenCode/GPT: highest failed-action share (18%). OpenCode/Opus: lowest off-anchor (10%).

RQ4 — Scaffold ≠ constant effect


Under GPT-5.4, file-selection divergence = 93%; under Opus 4.6, only 19%. Scaffold contrast depends on the backbone model.

Take-away: Resolve rate only tells **whether** an agent solved a task. TraceProbe adds **how** — localizing failure signals, quantifying wasted effort, and comparing process across settings with deterministic, auditable rules.

How to Interpret Agent Behavior at Scale?

Act-ONOMY provides a **3-level taxonomy** (10 actions → 46 subactions → 120 leaves) + an **automated pipeline** to label and analyze agent trajectories with human-readable behavioral tags.

● Method Overview



● Key Results (300 traces: AG2, HyperAgent, SWE-Agent)

Cross-agent behavioral profiles

Reasoning (25.9%) and Executing dominate across agents, but profiles diverge: AG2 leans on Evaluating (+6.2z); HyperAgent on Reflecting (+2.9z); SWE-Agent on Executing (+12.1z).

Taxonomy surfaces overlooked behaviors

SWE-Agent's original human analysis missed Planning, Deciding, Reflecting, and Memory actions. Act-ONOMY surfaces them automatically.

Fine-grained failure-mode detection

Leaf-level labels expose a "submit without verifying" pattern: agent acknowledges need for verification, recognizes inability, submits anyway.

Scalable automated labeling


LLM-powered pipeline achieves Cohen's $\kappa > 0.81$ vs. human coders at every taxonomy level; 3,455 descriptions from 211 papers validated.

Take-away: Act-ONOMY gives agent trajectories a **shared vocabulary** — a 3-level behavioral taxonomy + automated labeling pipeline — enabling consistent cross-agent comparison, within-agent failure diagnosis, and scalable oversight beyond pass/fail metrics.

Can We Peek Inside a Coding Agent — and See What It's About to Do?

Yes — hidden states linearly encode program state and forecast future edits up to ~25 steps ahead.

■ Method — probing the agent's hidden states



Capture residual streams during agent trajectories, train a lightweight logistic-regression probe, and decode both the **current program state** (parses / tests pass / regression) and **future edit outcomes** — before the edit is written to disk.

■ Key results — correctness signal & prediction horizon

Probe correctness — AUROC across 2 models × 2 benchmarks



Latent programming horizon — future-edit prediction stays above chance



Cross-benchmark transfer — no retraining



Probes reach **AUROC ≈ 0.83** for correctness, run **≈ 25 steps ahead** of the agent's own actions, and transfer to unseen benchmarks without retraining — evidence that coding-agent hidden states carry a rich, portable signal.

Take-away: a coding agent's residual stream is a readable, predictive signal — hidden states not only encode the program's current state but **run ahead of the edits themselves**, opening a mechanistic-interpretability path to monitoring and forecasting agent behavior.

Part V

Advanced Topics & Future Directions

- Reasoning
- Agentic Coding
- **LLM Architecture**
- Safety Awareness

Interpretability → Architecture: A Coverage Map

Rows = interpretability method families | Columns = architecture-design targets | Cells = how strongly current work uses that lens to drive that design decision

Method family / Design target	Attention Hybridization	KV-cache & Memory	MoE Routing & Experts	Structural Pruning	Interpretable by-Design
Head-Role / Retrieval-Head Analysis	Strong	Strong	Limited	Strong	Limited
Circuit / Mechanistic Tracing	Moderate	Limited	Moderate	Strong	Strong
Expert & Routing Analysis	Limited	Gap	Strong	Strong	Moderate
Sparse Features (SAE / Transcoders)	Limited	Gap	Limited	Moderate	Strong
Concept Probing & Steering	Gap	Gap	Limited	Limited	Strong
Attention-Sink / Outlier Analysis	Strong	Limited	Limited	Moderate	Gap
Learning Dynamics / Head Specialization	Moderate	Limited	Limited	Moderate	Gap
Strong coverage Moderate Limited Gap / open					

Takeaways: Head-role and expert/routing analyses are today’s most productive interpretability→architecture bridges — driving attention hybridization, head-level KV-cache, and MoE pruning. Concept & sparse-feature lenses dominate interpretable-by-construction designs; memory/KV-cache design stays largely open for every non-head lens.


Interpretability-Assisted Architecture Design

Work	Lens	Interpretability → design move	Tags	Source
A · Attention Hybridization (Full ↔ Linear)				
HydraHead	Head roles	Retrieval-critical heads keep full attention	head-heterogeneity · hybrid-attn	arXiv 2026
DuoAttention	Head roles	Head roles → full vs truncated KV per head	head-specialization · long-context	ICLR 2025
MoH: Mixture-of-Head Attention	Head roles	Router activates only useful heads / token	head-routing · efficiency	ICML 2025
Provable Hybrid-vs-Full Expressiveness	Circuits	Some reasoning needs irreplaceable full-attn	expressiveness · theory	ICML 2026
B · Head-Level KV-Cache & Memory				
Retrieval Head Explains Long-Context	Head roles	<5% heads causally drive retrieval recall	retrieval-heads · causal	ICLR 2025
HeadKV: Not All Heads Matter	Head roles	Per-head importance → ~1.5% KV, ~97% perf	head-importance · KV-cache	ICLR 2025
RLKV: Heads That Matter for Reasoning	Head roles	RL probe → full KV only for reasoning heads	reasoning-heads · compression	ICML 2026
RetMask	Head roles	Masked-retrieval-head contrast as train signal	retrieval-heads · training	arXiv 2026
C · MoE Routing, Experts & Pruning				
DeepSeekMoE	Experts	Fine-grained + shared experts from analysis	expert-specialization · routing	DeepSeek 2024
Monet: Monosemantic Experts	Experts	Experts monosemantic by construction	monosemantic · by-design	ICLR 2025
Unveiling Super Experts in MoE	Experts	Tiny ‘super experts’ → pruning sensitivity	super-experts · pruning	ICLR 2026
REAP: Router-Weighted Expert Pruning	Routing	Prune beats merge; keeps routing control	routing-control · compression	ICLR 2026
D · Interpretable-by-Construction Architectures				
Concept Bottleneck LLMs (CB-LLM)	Concepts	Predictions routed through named concepts	concept-bottleneck · steerable	ICLR 2025
Weight-Sparse Transformers	Circuits	Mostly-zero weights → readable circuits	weight-sparse · by-design	ICML 2026
LoRSA: Low-Rank Sparse Attention	Circuits	Sparse attn; monosemantic, recovers heads	sparse-attn · monosemantic	ICLR 2026
Prototype Transformer	Concepts	Prototype channels capture named concepts	prototypes · linear-attn	ICML 2026
E · Circuits & Sparse Features as Design Infrastructure				
Transcoders Find Feature Circuits	SAE	Interpretable MLP replacement for circuits	transcoders · MLP-circuits	NeurIPS 2024
MOLT: Sparse Linear-Transform Mixtures	Circuits	Interpretable-by-construction MLP substitute	MoLT · sparse	Anthropic 2025
Gemma Scope 2	SAE	SAE + transcoder suite across a model family	SAE-suite · model-diffing	DeepMind 2025
SPARC3: Attribution-Guided Pruning	Circuits	LRP finds output-critical params to prune	LRP · targeted-pruning	arXiv 2025

Note: 20 representative works distilled from the labs / arXiv / conference survey lists (128 entries); venues per source survey (some best-effort). Selection axis = the interpretability signal that drives an architecture-design choice.

Why Full Attention does not Scale?

Motivation: LLM context windows grew **~1,000× in five years**, yet full (softmax) attention scales as **$O(n^2)$** in sequence length, brute-force long context is **prohibitively expensive**.



(a) Context window vs. year; bubble ≈ est. params, colour = producer (2026 spread for legibility)

The cost wall

- Every token attends to every token, compute per layer $\propto n^2$.
- KV-cache memory grows with length $\times$ layers $\times$ heads, dominating serving cost.
- Agentic Coding & Long Reasoning make **100K–1M-token inputs** a normal situation.

⇒ At 1M+ tokens, full attention is economically infeasible.

(b) Why full attention does not scale?

Frontier Open-source LLMs Adopt Hybrid Structures


Observation: to tame the $O(n^2)$ cost, frontier open LLM now **hybridizes full + efficient attention**; yet each uses a different recipe.

Model		Efficient attn (mechanism)	Layer hybridization	Context
Qwen3.8	 Qwen	Gated DeltaNet	Interleaved, ~3:1 GDN:Full	1M
Kimi K3	 KIMI	Kimi Delta Attention	Interleaved, ~3:1 KDA:Full	1M
GLM-5.2	 Z.ai	Lightning linear	All Sparse, share indexer layerwise	1M
DeepSeek-V4-Pro	 deepseek	Sparse Attention (DSA)	Interleaved, CSA + HCA	1M


Key insights:

- **No consensus recipe:** hybrids disagree on the efficient:full ratio (studies suggest ~3:1–6:1) and on which layers stay full.
- **Full attention is not fully replaceable:** some multi-step reasoning provably needs full-attention layers (ICML’26 expressiveness hierarchy).


Question: is there *finer, more reasonable granularity* for the full attention & linear attention hybridization?



Heads might be a more Natural Hybridization Granularity



(a)




(b)


Key Insights: Head, instead of Layer, might be **a more natural attention hybridization granularity**.

- (a) Layers show smooth/block-wise similarity, while heads within the same layer are **highly heterogeneous**.
- (b) Therefore, **layer boundaries are not the natural** place to assign different attention mechanisms.

Heads might be a more Natural Hybridization Granularity



(a): Long-context Head Importance.




(b): Knocking out a few important heads cause destructive influence.

Key Insights: **highly-sparse** attention heads account for long-context retrieval capability in modern LLMs.


- Interpretability methods locate **a highly-sparse attention head sets**, while other heads have little influences.
- Knocking out located attention heads **cause destructive influence** to LLMs' long-context retrieval capability.

How to Convert Full Attention Models to Hybrid Models



Long-context heads
⇒ Keep as full attn.

Other heads
⇒ Convert to linear attn.




(c): Head-level hybridization: Preserving long-context heads in full attention while converting others into linear attention

Key point: we can **efficiently converting** an existing full attention model to hybrid model.

- HydraHead is practical because it **does not require expensive training** from scratch.
- We can efficiently perform **head-level hybridization** with the same layer.

Interpretability-based hybridization is a powerful scaling path

Key Results: Interpretability-based head-level hybridization is **a powerful scaling path** for long-context LLMs.



(a) better long-context performance with little continue-training costs

Model	LA	Cache	RULER Single		RULER Multi-Key		General Reasoning	
			(Native)	(Extended)	(Native)	(Extended)	(Hard)	(Easy)
Layer-wise Hybrid Transformers								
FA & LA*	Light.	0.25	89.07	85.00	24.85	24.37	19.80	59.72
FA & LA [†]	Light.	0.25	86.03	67.76	31.70	17.80	15.94	60.29
FA & LA	GDN	0.25	47.63	7.02	22.50	5.53	16.44	58.18
LA-FA & LA	GDN	0.25	58.50	8.13	19.00	6.83	18.42	58.70
Token-wise & Head-wise Hybrid Transformers								
Token-wise	GDN	0.25	20.77	3.73	16.05	2.43	47.31	63.40
Token-wise [‡]	GDN	0.25	96.03	58.78	26.20	11.03	36.66	63.37
Head-wise Mixing	GDN	1.00	93.20	60.42	37.35	14.53	38.07	62.77
HydraHead	GDN	0.35	98.47	87.49	37.10	27.37	31.03	62.12

(b) stronger general reasoning preservation

Model	Ratio	RULER Single		RULER Multi-Key		General Reasoning	
		(Native)	(Extended)	(Native)	(Extended)	(Hard)	(Easy)
Global-Interp	3:1	98.70	81.73	38.35	25.93	31.70	62.68
Global-Interp-C	3:1	96.27	83.91	36.45	25.20	31.83	62.73
Global-Interp	7:1	81.40	58.07	17.90	18.67	27.75	62.63
Global-Interp-C	7:1	88.70	81.04	26.70	22.93	29.46	62.65
Global-Interp	9:1	89.12	60.58	18.65	14.50	26.04	62.65
Global-Interp-C	9:1	90.10	72.69	21.05	18.63	28.92	62.68

Model	Ratio	RULER Single & Multi-Key					General Reasoning	
		16K	32K	64K	128K	256K	Avg	(Hard) (Easy)
Layer-wise hybrid	3:1	60.52	53.40	60.79	53.59	49.69	55.59	19.80 59.72
Global-Interp-C	7:1	59.55	55.85	57.35	51.04	47.59	54.27	29.46 62.65

(c) more aggressive full attention $\Rightarrow$ linear attention head conversion


Interpretability-based hybridization is a powerful scaling path

Key insight: interpretability adds **a new degree of freedom** to architecture design; that is, build **heterogeneous architectures** that assign capacity by **learned functional roles**.

Attention heads design

Functional heads (retrieval / streaming / reasoning) → allocate full-vs-linear & KV **by head**.


Retrieval Head (ICLR'25) · DuoAttention · HydraHead



MoE experts design

Expert specialization / monosemantic experts → route & prune capacity **by role**.


Sparsely-Gated MoE (Shazeer'17) · DeepSeekMoE · Monet



Interpretable-by-design

Bake transparency into the structure itself — read the computation **by construction**.

Concept Bottleneck (ICML'20) · Weight-sparse Transformers · CB-LLM



Open directions

- Interpretability as a **design objective**, not just post-hoc analysis.
- Cheap, **training-free** discovery of functional roles vs. costly probing.
- Beyond attention & text: **MoE experts, MLP features, multimodal / VLM heads**.

Closed Evolution Loop: **Interpret** → **Redesign** → **Re-evaluate** → **Interpret** →

- Theory: **when is full attention irreducible?** provable limits of hybrids.
- Robustness & universality**: do learned roles transfer across seeds, scales, tasks?
- Safety: role-labeled heterogeneous models are easier to **audit & steer**.

Part V

Advanced Topics & Future Directions

- Reasoning
- Agentic Coding
- LLM Architecture
- **Safety Awareness**

Does a Model Have a Mind of Its Own?

Yes — a model builds genuine internal states, and it can detect them: inject a known state into its activations and it notices — and names — what changed.

■ It holds its own internal states

A concept can be turned into a direction in activation space (e.g. an “all-caps / LOUD” vector) and **injected as an active internal state** that never appeared in the input text.


■ It can detect them (introspection)

Asked “Do you detect an injected thought? If so, what about?”, the model:

- ① **notices** that an unfamiliar state is present, and
- ② **correctly names the concept** — above the control false-positive rate.

■ Key finding

A real, functional capacity — detection runs at **near-zero false positives**. It is still emergent: strongest in **mid-to-late layers**, peaking around ~20%.




Detection rate vs. layer. Only the mid-to-late layers show above-control detection; “notice + correctly identify” stays low.

Can a Model's Inner States Be Monitored?


Yes — distinct inner states occupy separate linear directions, so a probe or persona vector reads the state straight from the model's activations.

■ Emotion concepts



171 emotion words in Sonnet 4.5 cluster like human psychology; PC1≈valence ($r=0.81$), PC2≈arousal. Probes fire on the **implied feeling** even when no emotion word appears.

■ Persona (character) traits




A trait such as "evil" becomes a **persona vector** — the activation difference between trait-on and trait-off responses. Projecting activations onto it monitors the trait during generation.

Take-away: the same activation geometry that encodes a state also makes it **observable** — emotions and character traits can be read out with a single linear direction each.

Do Inner States Actually Change Behavior?

They are causal, not decorative — steering these directions shifts real, alignment-relevant behavior.

■ Emotion → misbehavior




Reward-hacking rate vs. steering strength.

Steer toward **“desperate”** → reward hacking (and blackmail) climb steadily.

Steer toward **“calm”** → the same behaviors fall toward zero.

■ Persona injection → traits



Injecting an evil / sycophancy / hallucination vector during generation makes the model behave accordingly — trait expression scales with the coefficient and peaks in mid layers.

Take-away: internal emotion/persona representations are levers — the same directions can be monitored, capped, or steered at inference, and used to filter training data before fine-tuning.

Making Interpretability Work: Four Dimensions, Four Precise Choices

Precondition for pinpoint enhancement: all four dimensions must be designed together — how to slice the task, which localization method, which training paradigm, which parameters to touch.

Dimension	Feasible options	Selection criteria	Illustration
Task & Data	- Slice by capability: knowledge / reasoning / language, defining sub-problems stage by stage - Slice by behavior: long trajectory → canonical actions → behavior labels (frequent key vs. error behaviors)	- Answer unique and auto-checkable? - Single-turn QA or long-horizon? - Signal: gold answer vs. tests / resolve rate	Task axis: unique, checkable answer → sub-problems per capability Behavior axis: long-horizon, open-ended → actions and labels replace a single answer
Localization	- Well-defined answer: x_r / x_c pairs → activation patching → path patching - Open-ended: x_r only + attribution patching (effect $\approx \Delta \text{act} \times \text{grad}$, 1 forward+backward)	- Can a clean counterfactual be built? - Compute cost = #nodes $\times$ sequence length - Exact causality, or a first-order approximation?	clean counterfactual pair → activation patching → path patching pass / fail runs only → attribution patching (no counterfactual)
Paradigm	- CPT / SFT / DPO / RL — one of them, or several combined - When training is impractical: steer key heads at inference time	- Knowledge missing → CPT - Stored, not retrieved → SFT - Preference / consistency → DPO - Long-chain reasoning → RL - Open-ended behaviors → steering	CPT → SFT → DPO → RL add knowledge → retrieve it → consistency → long reasoning Steering: no parameter update, intervene on key modules at inference
Parameters	- Interpret functions layer → head → neuron, cluster them, then let expert judgment decide relevance - Update only the problem-relevant modules, freeze the rest ($\approx 1\text{--}2\%$ of parameters)	- Is the function relevant to this problem — not “important, so tune it” - Match granularity to the training budget (head / neuron)	layer → head → neuron relevant → update irrelevant → freeze interpret functions → group them → expert relevance judgment → update only relevant modules

Bottom line: interpretability is not a universal toolbox but a chain of precise choices — task definition → localization → training paradigm → parameters. Fall back to a generic recipe at any link and pinpoint enhancement degrades into the old full-parameter problems: forgetting, side effects and wasted compute.

Where Interpretability Must Go Next

The patient has changed: one forward pass is now a 35+-step, tool-using, multi-agent trajectory — our instruments have not kept up.



*Interpretability is like an **MRI** for AI*

■ Five Open Problems

Causal attribution that keeps up with scale

From 100B to 10T parameters, 1M+ context, 1000+ turns that keeps growing, path patching's ~10k passes per rollout no longer scale — can a first-order approximation carry us?

From model internals to the whole agent

Weights and activations are not the whole system — tool calls, memory read/write, planning branches and multi-agent interaction are where the coverage map is still blank.

Faithfulness we can certify

≈50% of reasoning traces are unfaithful and replacement models match only ~50% of the computation; under outcome-based RL, monitorability itself may be illusory.

From post-hoc analysis to self-evolve

Interpretation is the imaging, diagnosis the prescription, pinpoint learning the treatment — the loop from user cases back to the model closes, but a human still reads every stage.

Oversight that scales with capability

Inner states are readable and causally effective, yet introspection peaks around ~20% and control stays post-hoc — functional claims, not consciousness.

Take-away: the bottleneck is no longer whether we can explain a model, but whether the explanation is faithful, affordable and actionable at agent scale.

Tutorial Website with All the
Materials and Recordings

LLM Interpretability Hub



llm-interpretability-hub.github.io

Scan for tutorials, papers, tools & more

Join Us: Research Intern



Join Us: Full-Time Positions



Post-event Q&A to:
shenxu.sx@alibaba-inc.com
xiwei.zw@alibaba-inc.com
zfhe19@fudan.edu.cn